

## Adjustable-Head Construction Wrench



- Eliminates the need to carry several fixed-size wrenches.
- Forged from select alloy steel with continuous-taper handle.
- Industrial black finish for corrosion resistance.
- Handy lanyard hole (Cat. No. 3227).

| Cat. No. | Max. Size Capacity | Length       | Weight              |
|----------|--------------------|--------------|---------------------|
| 3239     | 1-1/2" (38 mm)     | 16" (406 mm) | 2.36 lbs. (1.07 kg) |
| 3227     | 1-5/16" (33 mm)    | 11" (279 mm) | 1.19 lbs. (0.54 kg) |



## Broad Head Bull Pins

- Forged, heat-treated bull pin increases efficiency and safety by providing a larger striking surface.
- Angled head and smooth blending of radii increase strength and reduce the danger of chipping.
- Below the head, squared-off shoulders have been forged to provide a surface for applying wrench to loosen wedged bull pins.
- Long, even taper reduces binding and hang-up.
- Added resistance to "mushrooming" permitting much longer use than is possible with conventional designs.
- Heat-treated for strength, black finish for rust resistance.



| Cat. No. | Top Diameter    | Point Diameter | Length           | Weight              |
|----------|-----------------|----------------|------------------|---------------------|
| 3255     | 1-1/4" (32 mm)  | 5/16" (8 mm)   | 13-3/4" (349 mm) | 2.90 lbs. (1.32 kg) |
| 3256     | 1-1/16" (27 mm) | 1/4" (6 mm)    | 10" (254 mm)     | 1.60 lbs. (0.73 kg) |

**Note:** OSHA 1926.301 (c) specifically states: "Impact tools, such as drift pins, wedges and chisels, shall be kept free of mushroomed heads."

## Ironworker's Pliers

- Twists and cuts soft annealed rebar tie wire.
- Hook bend handle.
- Spring-loaded action for self-opening.
- Heavy-duty knurled jaws.



| Cat. No.   | Overall Length  | Jaw Length       | Jaw Width       | Knife Length   | Weight              |
|------------|-----------------|------------------|-----------------|----------------|---------------------|
| D2000-7CST | 9-1/4" (235 mm) | 1-9/32" (33 mm)  | 1-5/32" (29 mm) | 5/8" (16 mm)   | 0.70 lbs. (0.32 kg) |
| D2000-9ST  | 9-3/8" (238 mm) | 1-19/32" (41 mm) | 1-1/4" (32 mm)  | 25/32" (20 mm) | 1.10 lbs. (0.50 kg) |

