

INNOVATOR

Handheld Thermometer

DP-350
DP-700



DP-350

 RoHS compliant

DP-700

 
 RoHS compliant

RKC RKC INSTRUMENT INC.



www.calcert.com

sales@calcert.com

1.888.610.7664

Simple Type Thermometer

Easy-to-use

DP-350

The DP-350 is an economical thermometer with a wide temperature range and useful functions, such as measured value and peak hold, sensor burnout, battery alarm, and automatic power off.

- No optional

Model Code :

DP-350*A

- With anti-shock cover (Silicon jacket)

Model Code :

DP-350*A-1

- With hard carrying case

Model Code :

DP-350*A-2

- With soft case

Model Code :

DP-350*A-3

* Temperature sensor is separately



Measured value display

HOLD : HOLD display

B.O : Burnout display

BAT : Battery low alarm display

POWER : Power ON/OFF key

HOLD : Measured value HOLD key

Measured Value Hold Function

Peak High & Low Temperature Function

Automatic Power OFF Function

Battery Low Alarm Function

Burnout (Sensor broken) Function


Temperature Sensor (Separately)

Many other types are available.

For static surface (Tilting Sensor Head Type)

Max. 300°C

Unit:mm




ST-230-K-1000-3C/F (For DP-350)
ST-230-K-1000-6C/F (For DP-700)

ST-230L-K-1000-3C/F (For DP-350)
ST-230L-K-1000-6C/F (For DP-700)

For High temperature static surface

Max. 600°C

Unit:mm



ST-32-K-1000-3C/A (For DP-350)
ST-32-K-1000-6C/A (For DP-700)

ST-32L-K-1000-3C/A (For DP-350)
ST-32L-K-1000-6C/A (For DP-700)

For semi-solid, viscous material and liquid

Unit:mm

JB-160




Max. 650°C
(ød=1.6)

JB-160-K-1.6-150-1000-3C/F (For DP-350, ød=1.6)
JB-160-K-1.6-150-1000-6C/F (For DP-700, ød=1.6)

Max. 750°C
(ød=3.2)

JB-160-K-3.2-150-1000-3C/F (For DP-350, ød=3.2)
JB-160-K-3.2-150-1000-6C/F (For DP-700, ød=3.2)

JB-16



Max. 650°C
(ød=1.6)

JB-16-K-1.6-100-1000-3C/A (For DP-350, ød=1.6)
JB-16-K-1.6-100-1000-6C/A (For DP-700, ød=1.6)

Max. 750°C
(ød=3.2)

JB-16-K-3.2-100-1000-3C/A (For DP-350, ød=3.2)
JB-16-K-3.2-100-1000-6C/A (For DP-700, ød=3.2)

JB-150 (Tip Sharpened Form) **Max. 400°C**



Tip Sharpened Form

Terminal Connector

Multi-Function Thermometer

Data logging function, Accuracy : $\pm 0.1\%$

DP-700

Model Code :

DP-700B/E

With USB

- Data Logging : 9999 logs
- Waterproof/Dustproof : IP54

Model Code :

DP-700A/E

No USB

- Data Logging : 99 logs
- Waterproof/Dustproof : IP67

• Temperature sensor is separately.

The DP-700 is a high accuracy thermometer with powerful functions, such as data logging, USB connection, peak high and low temperature, burnout (Sensor broken) display, remaining battery service display and automatic power off. The variety of functions supports you to manage temperature data efficiently.

Logging No./Total number of data points stored

Temperature gradient indications

Logging execution display

Burnout (Sensor broken) display

Remaining battery service life

Measured temperature

Message display

Data Logging (Recording), Max 9999 logs

Tag Number, User Name Function

Waterproof /Dustproof

Operation Lock Function

USB Function (Only for DP-700B)

Measured Value Hold Function

Peak High & Low Temperature Function

Automatic Power OFF Function

PV Bias, PV Digital Filter Function

Burnout (Sensor broken) Function

*1 DP-700A : 99 logs

*2 DP-700A : IP67
DP-700B : IP54

Easy to reading and manage data with PC



External Memory Device




USB

- By connecting DP-700B to USB port, a PC recognizes DP-700B as outside media.

* OS : Windows 10/8.1/7/Vista/XP

- Measured data can be stored in the file in the CSV format.



Measured temperature

F14n9-Oil

Comment
(Max. 11 characters)

Measured date and time
(Month, Day, Time)

(Day, Month, Time)

* Selectable

24/12 13:26

12/24 13:26

DP-700B stores up to 9999 points of logging temperature data including comment, measured date and time

DP-350 Specifications

Input • Range	Thermocouple : K (JIS/IEC) -200 to 1200°C (-199.9 to +199.9°C) -328 to 1999°F (-199.9 to +199.9°F)
Sampling time	Approx. 0.3 sec
Measuring accuracy	±(0.2% of indicated value + 1digit) or ±2°C (4°F) (Whichever is larger) • ±4°C (8°F) in the range of -100°C (-150°F) or less.
Display	Reflective TN LCD
Function	Peak high and low temperature, Measured Value Hold Function, Burnout (Sensor broken) Function, Decimal point selection (0/0.1), Battery Low Alarm Function, Automatic Power OFF Function (3min/30min/OFF)
Power supply	LR6 Alkaline battery x 2pcs. Life of battery : Approx. 1000 hours (Continuous operating time, Around the ambient temperature 23°C)
Operating environments	0 to 50°C (32 to 122°F), 45 to 85% RH
Net weight	Approx. 140g (Including LR6 Alkaline battery)
Accessories	LR6 (IEC and JIS) Alkaline battery., Hand strap

External Dimension

Unit:mm



■ DP-350 Optional

Anti-shock cover (Silicon jacket)



Hard carrying case



Soft case



■ DP-350 Model Code

Model Code	Accessory (Optional)
DP-350C*A	No optional
DP-350C*A-1	With anti-shock cover (Silicon jacket) *
DP-350C*A-2	With hard carrying case *
DP-350C*A-3	With soft case *

* Purchase of each cover only is available.
Refer to the following part numbers:
350P-K01: Anti-shock cover (Silicon jacket)
350P-K02: Hard carrying case
350P-K03: Soft case

DP-700 Specifications

Input • Range	Thermocouple K -200 to +1372°C (-328 to +2501°F) (Universal input) RTD Pt100 -199.9 to +999.9°C (-199.9 to +999.9°F) -200 to +850°C (-328 to +1562°F) -199.9 to +850.0°C (-199.9 to +999.9°F)
Sampling time	Approx. 0.5 sec
Measuring accuracy	±(0.1% of reading + 1digit) or ±0.3°C(±0.6°F) (Whichever is larger) Cold junction temperature error ±0.5°C(±0.9°F) [Between 5 and 40°C (41 and 104°F)] Ambient temperature influence ±0.01% of span / °C [Between 5 and 40°C (41 and 104°F)]
Display	Reflective FSTN LCD
Data logging (recording)	Recording method: Manual log mode : Can be manually recorded in the memory. Interval log mode : Can be automatically recorded (in a set interval) Interval time: 0 (Manual log mode), 1 to 3600 sec Recording items: Measured temperature, Date, Time, Tag name, User No. Recording capacity: DP-700A: Max. 99 logs DP-700B: Max.9999 logs Memory backup: DP-700A: Backed up by SRAM The recorded data may be lost if battery service life has expired or the battery is replaced. DP-700B: Backed up by EEPROM Number of writing : Approx. 100,000 times Data retaining period: Approx. 10 years
Tag number function	Number of maximum registration:DP-700A: 5 tags DP-700B: 99 tags Registration items: Tag name, evaluation points of high and low temperature Tag name: 11 characters (Numeral, Alphabets, Symbols) Memory backup: Same as Memory backup of data logging
User name function (Only for DP-700B)	Any user name can be registered for each user number. Logging data can store into register name. Number of maximum registration : 99 names. Number of character : 11 characters (Numeral, Alphabets, Symbols) Memory backup: Same as Memory backup of data logging
USB function (Only for DP-700B)	Interface: USB (Universal Serial Bus) Ver2.0 Communication speed: Full Speed compliant Connector type: USB series Mini-B Power supply: Bus power (The power is supplied from the USB port on the PC side. Device class: Mass Storage Class (Bulk-Only Transport) OS : Windows XP/Vista/7
Function	Peak high and low temperature PV bias: -99.9 to +99.9°C (°F) PV digital filter: 0 to 100 sec (0 : OFF) Calendar timer (year, month, date, hour, minute) Automatic Power OFF (1 to 60min/OFF) Decimal point selection (0/0.1), Temperature gradient indication
Waterproof and dustproof	DP-700A : IP67 DP-700B : IP54
Power supply	Type LR6 (based on IEC and JIS) alkaline battery, One battery Battery life: Approx. 400 hours (Continuous operating time, Around the ambient temperature 23°C)
Ambient temperature	-20 to +50°C
Ambient humidity	5 to 95%RH (Absolute humidity: Max. W.C 29g/m³ dry air at 101.3kPa.)
Weight	Approx.150g (Including LR6 Alkaline battery)
Accessories	LR6 (IEC and JIS) Alkaline battery, Strap, USB cable 1m (Only for DP-700B)

■ Cable adapter (For DP-700) Separately

3C (For DP-350 connector) to
6C (For DP-700 connector)

Model Code : A-DP700



• Only for thermocouple sensor

Microsoft, Windows, Excel are the registered trademark of Microsoft Corporation.
Company names and product names used in this brochure are the trademarks or registered trademarks of the respective companies.



- Before operating this product, read the instruction manual carefully to avoid incorrect operation.
- This product is intended for use with industrial machines, test and measuring equipment. It is not designed for use with medical equipment.
- If it is possible that an accident may occur as a result of the failure of the product or some other abnormality, an appropriate independent protection device must be installed.

Caution for the export trade

All transactions must comply with laws, regulations, and treaties.

Caution for imitated products

As products imitating our product now appear on the market, be careful that you don't purchase these imitated products. We will not warrant such products nor bear the responsibility for any damage and/or accident caused by their use.

RKC RKC INSTRUMENT INC.

