

Digital pH Meter DPH-2

Cat.No.4320

- Automatic Temperature Compensation!
- Waterproof design!
- Compact & portable design!
- Sturdy body design for electrode-protection
- Electrode can be cleaned with tap water
(Use of deionized water will damage the electrode.)



ATAGO®

Applications

- Food and beverage production control
- Brewing, fermentation, and food process control
- Soil-based agriculture and hydroponics
- Cutting oils, alkaline washing liquids
- pH levels of fruit juices
- Quality control for aquacultures and aquariums
- pH levels of boiler liquids
- pH levels of alkaline liquid
- Other soluble solutions

**Easy
one-handed
operation**



Specifications

Measurement range : 0.0 to 14.0pH
 Resolution : 0.1pH
 Measurement accuracy : ± 0.1 pH (2.0 to 12.0pH)
 Temperature compensation range : 0 to 50°C
 (Automatic Temperature Compensation)
 Calibration : 3-points (4.0, 7.0, and 10.0)
 Power supply : watch battery (LR44)1.4Vx4
 Materials in contact with the solution :
 Main body-ABS resin/Electrode-PBT resin
 International Protection class : IP67
 Dimensions & weight : 4.5x3.0x16.3cm, 90g

All ATAGO products are designed and manufactured in Japan.

ATAGO CO.,LTD.



HACCP GMP GLP

ATAGO products comply with HACCP, GMP, and GLP system standards.

* Specifications and appearance are subject to change without notice.



1.888.610.7664

www.calcert.com

sales@calcert.com