



Part code : 200-00020

The *LogTag® Protective Enclosure* is specifically designed for *LogTag®* recorder products to allow use in harsh environments.

The design of the enclosure minimises the effects of thermal lag caused by the additional casing. In general, the enclosure adds about 70% to the reaction time to temperature change for a given environment.

The enclosure's case is made from high impact polycarbonate plastic and is clear to allow viewing of the enclosed recorder's LCD or indicators.

Conservatively rated at IP67 (equivalent to NEMA6).

Supports *LogTag®* TRID30-7x, TRIX-8/16, SRIC-4, TRIL-8/SRIL-8 products.



Housing a TRID30-7



Housing a TRIX-8

Specifications

LogTag® part code	200-000020
LogTag® models supported	TRID30-7x, TRIX-8/16, SRIC-4, TRIL-8/SRIL-8
Storage temperature range	-40°C ~ +85°C (-40°F ~ +185°F)
Environmental protection rating	IP67 (equivalent to NEMA6) for temperatures 1°C~+40°C (33°F~+104°F)
Case material	Clear Polycarbonate with silicon rubber seal
Chemical resistance	In general the polycarbonate material can withstand alcohols and diluted acids well. Problems can occur with hydrocarbons, phenols, esters, ketones and alkalis especially at elevated temperatures.
T90 thermal performance	With TRIX-8 in 1 m/s air : T90 = ~ 10 minutes. With TRID30-7x in 1 m/s air : T90 = ~ 17minutes
Size	104mm (L - not including lug) x 76.5mm (W - including clips and hinge) x 13mm D
Weight	41grams