PRO-HOOD® ARC FLASH PROTECTION HOOD

8 - 100 CAL/CM²

PRO-HOOD® ARC FLASH PROTECTION HOODS ▶

8 cal/cm² to 100 cal/cm²* ATPV ratings

8 cal/cm² to 75 cal/cm²* hoods are made from arc flash resistant material

100 cal/cm²* hood is made from TuffWeld® and Q/9® material layers

Sewn with Nomex® thread

Arc rated 10" x 20" anti-fogging replaceable lens

Slotted bracket

Hook and pile tabs to attach Salisbury's PRO-AIR™ belt mounted
    compact air system

One size fits all.

Hard hat not included.

Meet current ASTM F2178 and NFPA 70E standards and the
    flammability requirements for ASTM F1506.

All PRO-HOODs are CE 0120 certified.

Orange color available by special order

NEW Optional Universal Inner Anti-Fog Lens
    (see page 12 for more information)

NEW Optional Integrated Air Flow Hood System
    (see page 17 for more information)

IMPROVEMENTS:

NEW Design and Cut on FH8BL. FH11BL & FH20BL

Clearer Lens available on FH8BL, FH11BL, FH20BL, FH31RB,
    FH40GY, FH40GYLT, and FH55GY

IMPROVED

IMPROVED LENS CLARITY!

FH31RB

**40 CAL/CM² & 100 CAL/CM².
LIGHTER MATERIAL THAN EVER.**

FH40GY

NEW

NEW AIR FLOW SYSTEM
OPTIONAL INTEGRATED
LIGHTWEIGHT AIR SYSTEM

Cat. No.	Description
FH8BL	IMPROVED 8 cal/cm², navy blue
FH11BL	IMPROVED 12 cal/cm², navy blue
FH20BL	IMPROVED 20 cal/cm², navy blue
FH31RB	IMPROVED 31 cal/cm², royal blue
FH40GY	IMPROVED 40 cal/cm², gray
FH40GYLT	IMPROVED 40 cal/cm², lighter weight, gray
FH55GY*	IMPROVED 55 cal/cm², gray
FH75GY*	75 cal/cm², gray
FH100TW*	100 cal/cm², khaki, TuffWeld®

Add suffix "-C" to include integrated air flow hood system.

NOTE: Available in orange upon request. Contact your local Salisbury Representative.

SALISBURY ADVANTAGE

NO OTHER OPTION COMES CLOSE!

FH8BL

NEW

NEW PRO-HOOD® CLEAR
IMPROVED FH8BL
-CLEAREST HOOD AVAILABLE
-LIGHTER WEIGHT
-MEETS NFPA 70E HRC2* 2009

*IMPORTANT: NFPA 70E does not have a Hazard Risk Category above 40 cal/cm². Working on levels above 40 cal/cm² should be avoided, because of the blast hazards caused by arc flash