

Part No.

FLP1-GR-QM-W1

FieldLab Pressure, 3000 psi / 200 bar / 20 MPa, Male Quick-test bottom connection, wireless module installed

A revolutionary pressure calibration platform that transforms the way field and laboratory technicians do their job. By putting the instructions on how to do the test directly onto the FieldLab the user is now in much better control of the situation.



FLP1-GR-QM-W1

Specs/Attributes

Accuracy - Pressure Measurement	+/- 0.02% of Full Scale (0-20% of Full Scale), +/- 0.1% of Reading (20-100% of Full Scale)
Battery Count	1
Battery Life	1000 Hours
Battery Type	Lithium Ion rechargeable, 4.8 Ah Capacity
Burst Pressure	12000 PSI / 825 bar / 83 MPa
Calibration Certificate	NIST traceable (included)
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, North America - Class 1 Division 1 Groups A-D, T4, (-10 < Ta < 50 °C), ATEX - Ex II 1 G Ex ia IIC T4 Ga (-10 < Ta < 50 °C), IECEx - Ex ia IIC T4 Ga (-10 < Ta < 50 °C), UN/DOT 38.3 (Lithium Batteries), Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country Adapters	North America, Europe, United Kingdom, Australia, China
Country of origin	USA
Datalogging	2 million points (onboard)
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, ftH2O @39°F, cmHg @ 0°C, oz / in^2
Harmonized Code	9026.20.0000

Specs/Attributes

LCD Display	3.5 in / 90mm Color TFT LCD Display
Materials	316 Stainless Steel, Reinforced Polyamide
Max Operating Temperature	120 °F / 50 °C
Max Pressure	3000 PSI / 200 bar / 20 MPa
Max Storage Temperature	165 °F / 75 °C
Measurement Type	Gauge Pressure
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	14 °F / -10 °C
Min Storage Temperature	-20 °F / -29 °C
Mounting Holes	3 x M5 Inserts (10 mm deep)
Operating Altitude (max)	10,000 ft (3050 m)
Power Input	90-264 VAC, 50-60 Hz
Primary Power	Battery Power
Process Connection	Male Quick-test
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
Seal Materials	Teflon, Viton
Sensor Type	High Precision MEMS
Temperature Compensation	14 to 122°F (-10 to 50°C)
USB Connection	USB (Type B)
W1 Radio Installed	Yes
Wetted Materials	316 Stainless Steel
Wireless Range	500 ft / 155 m
Connector End 1	Male Quick-test
Weight	2.58 lbs / 1.17 kg
Dimensions	H: 9 in (22.86 cm) x W: 5 in (12.7 cm) x D: 2.5 in (6.35 cm)