


LEAKChecker

FIND LEAKS... CUT COSTS



Focused

Compressed air leaks are a senseless waste of energy. Find and fix them fast with LEAKChecker; an ultrasound solution focused on reducing waste and saving you money.

Simple

LEAKChecker is so easy to use. Simply open the box, switch it on, and start finding leaks. Enjoy crystal-clear sound in the headset and a vibrant colour display. LEAKChecker makes leak surveying fun again.

Affordable

Air leaks are an expensive problem... and LEAKChecker is the affordable solution. Built with SDT quality, it's offered at a price that will leave you speechless.

Create leak reports fast with



Download for free



Description

LEAKChecker is an ultrasound solution designed to find compressed air and vacuum leaks in noisy environments. Measure the level of the leak with LEAKChecker, then estimate its cost impact with the LEAKReporter App, available for free on the App store. LEAKChecker comes with a 16mm diameter replaceable ultrasound sensor.

Kit Contents

- LEAKChecker
- USB Cable
- Headphones
- Screwdriver
- 2 AA Batteries
- Carrying case



| General | |
|--|---|
| Function | Ultrasound measurement device |
| Display | 160x128 pixels Color OLED |
| Keyboard | 5 function keys |
| Typical measurement range | -6 to 99.9 dB μ V (reference 0 dB = 1 μ V) |
| Resolution | 0.1 digits |
| Measurement bandwidth | 35 to 42 kHz |
| Signal amplification | +30 dB (built-in sensor gain) to +102 dB by step of 6 dB |
| RMS period time | 250 milliseconds (main screen) / 3 sec (bar graph) |
| Sampling frequency | 64 kHz |
| ADC Resolution | 12 bits |
| Minimum sensitivity | -31dB (@40 kHz, 0 dB-1 V/ μ bar) |
| Environmental | |
| Operating temperature range | -10 to +50 °C 14 to 122°F |
| IP rating | IP42 |
| Standards | EN 61326-1:2013, EN 55011:2016 + A1:2017, EN 61000-4-2:2009, EN 61000-4-3:2006 + A1:2008 + IS1:2009 + A2:2010 |
| Mechanical | |
| Housing material | ABS |
| Dimensions housing | 158x59x38.5 mm 6.22"x2.32"x1.51" |
| Flexible rod length (Removable sensor) | 445 mm 17.51" |
| Weight | 350g 12.35 oz |
| Battery/Utility connector | USB Mini-B 5-pin |
| Power | |
| Battery | 2 AA batteries |
| Autonomy | 7 hours |
| Audio | |
| Operable with | SDT provided head set only |
| Maximum audio output (protection) | +83dB SPL with SDT headset |
| Headset | 25dB NRR Peltor HQ headset |

The SDT Checkers Range: Ultrasound detectors for every application and budget.

LEAKChecker: Find compressed air and vacuum leaks.

TRAPChecker: Assess the condition of traps and valves.

LUBEChecker: Optimize bearing lubrication.

TIGHTChecker: Verify the tightness of closed volumes.

HATCHChecker: When hatch cover tightness matters.

ULTRAChecker: Check everything.



SDT: leader in acoustic detection for industrial maintenance

SDT provides ultrasound solutions that help our customers gain a better understanding about the health of their factory. We help them predict failures, control energy costs, and improve product quality while contributing to the overall reliability of their assets.



**Ultrasound
Solutions**

The LEAKChecker is part of the SDT product range that combines robustness and high performance. It is available through our worldwide authorized distributor network.