

Gasman

Personal
Rechargeable
Single Gas
Monitor

Robust
Effective warning
Flexible
User-friendly



Gasman

Personal Rechargeable Single Gas Monitor

Gasman is a rugged, compact single gas personal monitor designed for use in the toughest environments.

With impact-resistant construction and compliance to IP65, Gasman offers a wide range of gases, including six flammable calibration options. Gasman gives an unbeatable combination of powerful loud and bright alarms. Its stunningly compact and lightweight design makes it ideal for use in industries such as oil and gas, chemical, steel works and waste and water works.



Robust

Tough polycarbonate housing

Protects you in the harshest environments

Water and dust resistant to IP65

Full overmolding

High impact resistance

Effective warning

2 levels of instantaneous alarm and TWA alarms for toxic versions

Ensures prompt evacuation from hazardous zone

95dB audible alarm

Vivid twin red/blue visual alarm

If ambient noise is high, Gasman still alerts you by vibrating and with the high impact blue/red LED alarms

Internal vibrating alarm

Flexible

Versions available for flammable gas, oxygen and toxic gases

Gas detector tailored to your requirements

Rechargeable versions for all gas types

Non-rechargeable versions for oxygen and toxic gases

Real time TWA and peak display options

Fully interchangeable intelligent sensor modules

User-friendly

One button operation

Quick and easy to use

Backlit display for gas diagnostics and operating status

Easy to read

Ultra lightweight- just 85g for toxic versions

Comfortable to wear

Next Generation of Sensor Innovations



Long-Life Oxygen

- Industry's first 5-year warranty
- Lead-free for RoHS compliance
- Reduced sensor replacement
- Lower cost of ownership
- Reduced environmental impact



MPS Flammable

- First to market single gas personal device
- Significant safety value add
- 5 year sensor warranty
- Hydrogen ready
- True LEL multi-gas accuracy

To read more on Crowcon Connect and what it can do, please visit our website or download our Connect brochure.



Typical ranges and alarms

Gas	Range	Typical alarms
Ammonia (NH ₃)	0-1000 ppm	25 ppm
Carbon monoxide (CO)	0-500 ppm	20 ppm
Carbon dioxide (CO ₂)	0-5%	0.5%
Carbon monoxide (H ₂ filtered)	0-1500 ppm	20 ppm
Chlorine (Cl ₂)	0-20 ppm	0.3 ppm
Chlorine Dioxide (ClO ₂)	0-1 ppm	0.1 ppm
Ethylene Oxide (ETO)	0-10 ppm	3 ppm
Flammable	0-100% LEL	20% LEL
Flammable (MPS)	0-100% True LEL	20%LEL
Fluorine (F ₂)	0-1 ppm	0.5 ppm
Hydrogen (H ₂)	0-2000 ppm	N/A

Gas	Range	Typical alarms
Hydrogen cyanide (HCN)	0-25 ppm	5 ppm
Hydrogen fluoride (HF)	0-10 ppm	1 ppm
Hydrogen sulphide (H ₂ S)	0-250 ppm	5 ppm
Nitric oxide (NO)	0-100 ppm	25 ppm
Nitrogen dioxide (NO ₂)	0-20 ppm	0.5 ppm
Oxygen (O ₂) Long-Life	0-25%	19.5%/23.5%
Oxygen (O ₂)	0-25%	19.5%/23.5%
Ozone (O ₃)	0-1 ppm	0.1 ppm
Phosphine (PH ₃)	0-5 ppm	0.1 ppm
Phosgene (COCl ₂)	0-1 ppm	0.02 ppm
Sulphur dioxide (SO ₂)	0-20 ppm	0.5 ppm

Further gas types will be available - contact Crowcon with your requests.

Disclaimer

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement Crowcon Detection Instruments Limited reserves the right to make product changes without notice. The products are routinely subject to a programme of testing which may result in some changes in the characteristics quoted. Technical information contained in this document or otherwise provided by Crowcon are based upon records, tests, or experience that the company believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed.

Many factors beyond Crowcon Detection Instruments' control and uniquely within user's knowledge and control can affect the use and performance of a Crowcon product in a particular application.

As the products may be used by the client in circumstances beyond the knowledge and control of Crowcon Detection Instruments Limited, we cannot determine the relevance of these to an individual customer's application. It is the clients' sole responsibility to carry out the necessary tests to evaluate the usefulness of the products and review all applicable regulations and standards to ensure their safety of operation in a particular application.

Specification

Size	90 x 48 x 24 mm (3.5 x 1.9 x 0.95 ins)	
Weight	Flammable Toxic Oxygen Carbon dioxide Oxygen Long Life	138g (4.9oz) 85g (3oz) 129g (4.6oz) 139g (4.9oz) 90g
Typical response times (T_{90})	Flammable Toxic gas Oxygen Oxygen (Long-Life)	20s 20s 10s 10s
Alarms	Audible	95dB Multiple alarm options let you select distinctive tones for different alarm levels
	Visible	Dual colors red/ blue flashing LEDs in a gas hazard
	Vibrating	Internal vibrating alarm
Display		Custom LCD with backlight and display of gas concentration. Graphic symbols for battery (with proportional indication of remaining operation time), and display mode. Start-up indication when calibration is due within 30 days, calibration overdue or service required.
Display modes	Normal display Display recall	Real time gas concentration levels Peak readings and TWA
Datalogging		Full timed data logging with adjustable sample rate, set to 1 min. data rate as default. 900 hours storage at 1 min. interval (54,000 logs), >4800 events
Battery	Rechargeable	Lithium battery for all gas types
	Non-rechargeable	Lithium battery for toxics and oxygen (excluding CO ₂)
Operating time*	Rechargeable	172 hours for MPS flammable
	Non-rechargeable	Up to 2 years
Sampling		Optional manual aspirator
Operating temperature range**		-20°C to + 65°C (-4°F to +149°F)
Humidity		5-95% RH 0-99% RH (O ₂ , LL, MPS)
Ingress protection		IP65
Approval codes	Europe	Toxic or O ₂ : ATEX II 1G Ex ia db IIC T4 Ga (-4°F ≤ Ta ≤ +149°F) BASEEFA04ATEX0384 Flammable: ATEX II 2G Ex ia d IIC T4 Gb (-4°F ≤ Ta ≤ +149°F) BASEEFA04ATEX0383 Flammable (MPS): ATEX II 1G Ex ia IIC T4 Ga (-20°C ≤ Ta ≤ +65°C) BASEEFA04ATEX0383
	International	Toxic or O ₂ : IECEx Ex ia IIC T4 Ga (-4°F ≤ Ta ≤ +149°F) BAS05.0039 Flammable: Ex db ia IIC T4 Gb (-4°F ≤ Ta ≤ +149°F)
	North America	CSA Class 1, Division 1, Groups A, B, C, D
Standards safety	Europe North America	EN60079-0, EN60079-11, EN60079-1, 2014/34/EU CSA22.2 Atex 2014/34/EU
Operation standards		EN50270
PC interface		RS232 connection from 'Charger/interface' variation RS232/USB converter available
Calibration		Gasman can be routinely calibrated using Portables PC software
Accessories		Gasman is supplied with an integral alligator clip. Optional accessories: gas test kit, Gasman external filter, leather carrying case, single-way charger, charger interface software and communication kit (excluding PSU), 5 way multi-charger
Crowcon Connect Compatible?	Yes	

*Operating time will depend on operating pattern and alarm occurrence. Frequent or long lasting alarms and use of the optional confidence beep will reduce battery life.

**Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods.