



Personal Monitor
For oxygen, toxic
or flammable gases

Gasman

A personal monitor you can trust

Gasman sets new standards for personal gas monitors for flammable, oxygen and toxic gases. Designed for use in the toughest environments Gasman offers an unbeatable combination of powerful loud and bright alarms with a stunningly compact and lightweight design.

Together with its rugged impact resistant construction and compliance to IP65 and IP67 Gasman is the ideal choice for personal monitoring in demanding industrial environments.

Simple

- True one button operation
- Easy to read LCD display with backlight
- Clear indication of operating status
- 30 Days advance calibration due warning

Assurance

- 95dBA audible alarm
- Striking twin red/blue visual alarm
- Internal vibrating alarm
- 2 levels of instantaneous alarm
- Time weighted average alarms for toxic versions

Robust

- Tough polycarbonate housing
- Full elastomeric overmoulding
- High impact resistance
- IP65 and IP67 compliant

Flexible

- Fully interchangeable i-module sensors
- Flammable toxic and oxygen sensors available
- Rechargeable version for all gas types
- Dry cell versions for toxics and oxygen
- Data and event logging

Specification

Weight	130g flammable 95g oxygen 80g toxic	Battery Types	Rechargeable Li-ion battery for all gas types Non rechargeable Lithium battery for toxics and oxygen
Dimensions	90x48x24mm (3.5x1.9x0.95inch) HxWxD		
Typical ranges and alarms			
Gas	Range	Alarm UK and ROW	Alarm US
Flammable	0-100% LEL	20% LEL	10% LEL
Oxygen	0-25%	19.5/23.5%	19.5%
Hydrogen Sulphide	0-100ppm	5ppm	10ppm
Carbon Monoxide	0-500ppm	30ppm	35ppm
Sulphur Dioxide	0-20ppm	1ppm	2ppm
Chlorine	0-20ppm	0.5ppm	0.5ppm
Nitrogen Dioxide	0-20ppm	1ppm	3ppm
Ammonia	0-100ppm	25ppm	25ppm
Ozone	0-1ppm	0.1ppm	0.1ppm
Hydrogen	0-1000ppm	N/A	N/A
Hydrogen Cyanide	0-25ppm	5ppm	5ppm
Hydrogen Chloride	0-30ppm	1ppm	1ppm
Hydrogen Fluoride	0-10ppm	5ppm	5ppm
Phosphine	0-5ppm	0.2ppm	0.2ppm
Fluorine	0-1ppm	0.1ppm	0.1ppm
Phosgene	0-1ppm	0.1ppm	0.1ppm
Ethylene Oxide	0-10ppm	5ppm	5ppm
Nitric Oxide	0-100ppm	25ppm	50ppm
Other ranges and alarm levels are available on request. Each unit can have two instantaneous alarms levels set. Toxic units also have Time Weighted Average alarms.			
Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.			
Typical response times	Flammable 20s, Toxic gas 20s, Oxygen 10s		
Audible Alarms	95dBA Multiple alarm sounds allow selection of distinctive tones for different alarm levels.		
Visible Alarms	Dual colour red/blue flashing LEDs in gas hazard		
Vibrating Alarm	Internal vibrating alarm		
Display	Custom LCD with backlight, with display of gas concentration. Graphic symbols for battery (with proportional indication of remaining operation time), and display mode. Start up indication when calibration is due within 30 days, calibration overdue, or service required.		
Display Mode	Normal display for real time gas concentration levels. Display recall for Peak readings and TWA.		
Datalogging	Full timed datalogging with adjustable sample rate, set to 1 minute data rate. 900 hours storage at 1 minute interval. >4800 capacity event logging to record all instrument events including: Switch on/off, Battery status, Alarms activate/clear including peak values of response, Gas Test pass or fail. All events are time stamped		
Optional accessories include: alligator clip, hard hat harness, universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing) and Gas Test Kit.			
Gasman is also available as an uncertified CO ₂ version. See separate datasheet			

A HALMA COMPANY

