

Item # GSCP-200202-5, 2 in. Stainless Steel Precision Sanitary Clamp Flowmeter

This 2 in. Tri-Clover Sanitary meter is for applications that do not require a 3A Approval. Comes with a GG510 standard display.

**Specifications**

Design Type	Turbine
Inner Diameter	2 in.
Fitting	Sanitary Clamp 2 in.
Accuracy	±0.5 % Linearity
Flow Range	33 to 330 GPM 125.0 to 1250 LPM
Repeatability	±0.1 %
Operating Temperature	-100 to +185 °F -74 to +85 °C
Frequency	100 to 1000 Hz
Recommended Strainer Size	14 mesh
Display	LCD - GG510 Transmitter
Reads	Gallons Litres
Electronic Choice	GG510 - Standard Display (Local) GA500 (Remote) GG500 (Remote) GX500 (Remote) SC500 (Remote)
Sensor	Standard Pickup
Pressure Rating	Limited by fitting size, clamp size & temp.
	316 Stainless Steel Housing CD4MCu Stainless Steel Rotor

Wetted Materials	316 Stainless Steel Rotor Supports 316 Stainless Steel Shaft PTFE Sleeve Bearings 440C Stainless Steel Thrust Bearings
Typical K-Factor	181
Model	GSCP-200202-5
Approvals	N.I.S.T.
Popularity	Most Popular