

# HF5 TRANSMITTER



## BENEFITS

- Measures relative humidity, temperature and dew point
- Absolute repeatability guaranteed
- Freely programmable and scalable analog outputs

## APPLICATIONS

- Heating, ventilation, air conditioning
- Food industry
- Pharmaceutical industry
- Printing and paper industries



### Proven housing

- Robust, industrial-quality housing
- Wall or duct mounting possible

### Power supply

- 15...40 VDC/12...28 VAC
- 9...36 VDC/7...24 VAC (galvanically isolated)
- 100...240 VAC (galvanically isolated)
- Power over Ethernet (PoE)

### Outputs

- The 2 analog outputs are freely selectable and scalable
- **2-wire** (HF52), **3/4-wire** (HF53) and 3/4-wire (HF54, HF56 with galvanic isolation) versions available
- Optional digital outputs allow networking via RS-485, Ethernet and even wireless
- Combined digital and analog output signals allow simultaneous control and monitoring of a device by just one transmitter

### Flexible choice of probes

- Connection of a wide range of probes possible
- Connection of simulators facilitates process validation



## APPLICATIONS

### HF5 WALL VERSION

Use in  
technical rooms

HF52/53/54 series



HF53S/54S series



HF56 series



### HF5 DUCT VERSION

Use in  
ventilation shafts



## PROBES FOR HYGROFLEX TRANSMITTERS

### STANDARD CLIMATIC PROBE

Range of application: - 50...100 °C

Variants: Plastic and stainless-steel versions



### INDUSTRIAL PROBES

Range of application: - 100...200 °C

Material: Stainless steel




Order Code	Type	Accuracy @ 23 °C	Application Range	Sensor Element	Long-Term Stability	
HC2A-IC	Industrial probe	±0.8 %RH ±0.1 K	-100...200 °C	HYGROMER HT-1	<1 %RH / year	
HC2A-S	Standard probe, black		-50...100 °C 0...100 %RH			
HC2A-S3	Meteo probe, white		HYGROMER HH-1			
HC2A-SM	Steel probe					
HC2A-S-HH	Standard probes for harsh environments	±1.2 %RH ±0.1 K				
HC2A-SM-HH						

You can find further information on the probes at our website: HC2A - Datasheet


# TECHNICAL INFORMATION

## HF52/53/54 series



Wall version (W)






Duct version (D)



## HF56 series



## HF53S/54S series



	HF52 2-wire	HF53/54/56 3/4-wire
<b>Humidity probe</b>	HygroClip2 probes, various types*	
<b>Probe cable extension</b>	Passive: max. 5 m, active: 100 m	
<b>Accuracy at 23 ± 5 °C</b>	Probe dependent	
<b>Response time τ 63</b>	Probe dependent	
<b>Initialization time</b>	HF53/54/56 typically 3 s, HF52 typically 60 s	
<b>Measurement range</b>	Probe dependent	
<b>Range of application electronics</b>	HF53/54/56: -40...60 °C / 0...100 %RH (-10...60 °C with LCD)	
<b>Display type (option) (HF52: without backlight)</b>	Graphic with backlight Display freely configurable	
<b>Trend indicator</b>	Yes	
<b>Output signals (analog)</b>	Freely scalable by user 0...1 V, 0...5 V, 0...10 V, 0(4)...20 mA	
<b>Digital outputs (optional)</b>	Ethernet (LAN, WLAN), USB, RS-485	
<b>Power supply</b>	HF52: 10...28 VDC: 10 V + (0.02 x load) HF53: 15...40 VDC/12...28 VAC HF54 with galvanic isolation: 9...36 VDC HF56 with galvanic isolation: 100...240 VAC	
<b>Current consumption</b>	HF52: max. 40 mA, others <100 mA, LAN option <300 mA	
<b>Circuit type</b>	HF52: 2 x 2 wires HF53/54/56: 3/4 wires	
<b>Load per analog output</b>	V-signal: ≥1 kΩ/V / mA-signal: ≤500 Ω	
<b>Load compensation</b>	Yes	
<b>Firmware upgradable</b>	Yes, via HW4 software	
<b>Sensor diagnostics (drift, state)</b>	Programmable. Default: Off	
<b>Humidity adjustment</b>	Keyboard/Software: multipoint (HF53/54/56)	
<b>Temperature adjustment</b>	Keyboard: 1-point Software: 2-point (HF53/54/56)	
<b>External memory function for logging</b>	Yes, 2000 data point memory	
<b>Psychrometric calculations</b>	All	
<b>PC interface, UART</b>	Yes, HW4-compatible	
<b>Data processing via HW4</b>	Graphics, statistics, analyses, qualification, etc.	
<b>Housing material</b>	ABS / Aluminum (HF5xxS)	
<b>Cable connections</b>	1 x M16 x 1.5, to terminals	
<b>Standards</b>	CE conformity 2014/30/EU	
<b>Audit trail, electronic records</b>	Conforms to FDA 21 CFR Part 11 and GAMP	
<b>IP protection &amp; fire protection class</b>	IP65 / Corresponds to UL94-HB	

\* HF520 transmitters are not compatible with metal industrial probes

# ORDER CODE

Power supply and output signal type									
Supply voltage	Type	Output							
2-wire (only display without backlight, digital interface not possible)									
10...28 VDC	2-wire	4...20 mA	HF520-						
Low voltage, 3-wire									
18...40 VDC / 13...28 VAC	3-wire	4...20 mA	HF532-						
18...40 VDC / 13...28 VAC	3-wire	0...10 V	HF535-						
Low voltage, 4-wire, galvanically isolated									
9...36 VDC / 7...24 VAC	4-wire	4...20 mA	HF545-						
High voltage, 4-wire, galvanically isolated (in HF8 housing)									
100...240 VAC	4-wire	4...20 mA	HF565-	W					
Device type / Mechanical installation									
Duct probe, probe length Ø 15 x 208 mm					D				
Wall probe, probe length Ø 15 x 85 mm					W				
Output parameters									
Humidity & temperature (humidity always 0...100 %RH)					B				X X
Humidity & specific humidity (Q) in g/kg					4	X X			
Humidity & mixing ratio (R) in g/kg					6	X X			
Temperature & dew point					A				
Temperature & wet-bulb temperature (Tw) in °C					C				
Temperature & enthalpy (H) in kJ/kg					D				
Temperature & specific humidity (Q) in g/kg					E				
Temperature & mixing ratio (R) in g/kg					G				
Output scaling of temperature (humidity always 0...100 %RH)									
No temperature output					X X				
0...50 °C					1 X				
0...100 °C					A 3				
0...150 °C					D 6				
-40...60 °C					3 X				
-30...70 °C					4 X				
-40...85 °C					5 X				
0...100 °C					6 X				
Optional display									
Display (only for horizontal mounting)							D		
No display (vertical mounting always without display)							X		
Electrical connections / Interface configuration / Mounting type									
Cable gland	Mounting	Display							
Analog signals to terminal									
1x M16 / 2x M16 in HF56x	Horizontal	Possible							1
1x M16	Vertical	Not possible		D				X 2	
Analog and feed signal to terminal									
Tuchel T7 connector, direct	Horizontal	Possible	HF53x						F
			HF54x						
RS485 to terminal & analog signal to terminal									
2x M16	Horizontal	Possible	HF53x						H
			HF54x						
			HF562						
Ethernet RJ45 & RS485 to terminal & analog signal to terminal									
1x M16 / 2x M16 in HF56x	Horizontal	Possible	HF53x						L
			HF54x						
			HF562						
Scaling of calculated parameters									
No calculation									X X
0...20									1 X
0...25									2 X
0...50									3 X
0...100									4 X
-50...200									D X

