

Economical Handheld Thermometers

OMEGATEMP®

- ✓ Lightweight Design
- ✓ Pocket Hook and Magnet Hanger
- ✓ MAX/DATA HOLD Function

HH67



HH67 shown smaller than actual size.

HH67 Semiconductor Thermometer with Probe Attached

Specifications

Temperature:

Range: -50 to 150°C (-58 to 302°F)

Resolution: 0.1°C (1°F)

Accuracy:

- ±3.0°C from -50 to 0°C
- ±1.5°C from 0 to 100°C
- ±3.0°C from 100 to 150°C
- ±6.0°F from -58 to 32°F
- ±3.0°F from 32 to 212°F
- ±6.0°F from 212 to 302°F

Sensor: Semiconductor, silicon diode type

Dimensions: 160 H x 48 W x 24 mm D (6.3 x 1.9 x .94")

Weight: Approx 98 g (3.5 oz) including battery

Probe: Stainless steel

Probe Diameter: 3.2 mm (1/8") with pointed tip

Probe Length: 130 mm (5.1")

Display: 3 1/2 digit liquid crystal display (LCD)

Low Battery Indication: The "⚡" is displayed when the battery voltage drops below the operating level

Measurement Rate: 2.5 times/second

Operating Environment: 0 to 50°C (32 to 122°F) <70% RH

Storage Environment: -20°C to 60°C (-4 to 140°F), 0 to 80% RH with battery removed from meter

Accuracy: Stated accuracy at 23°C ±5°C (73°F ±9°F), <75% RH

Battery: 1.5V x 3 pcs "AAA" size (not included)

Battery Life: 140 hours (continuity) typical

Applications

- ✓ Greenhouses
- ✓ Office Environment
- ✓ Department Stores
- ✓ Labs
- ✓ Weather Monitoring
- ✓ Art Galleries
- ✓ Museums
- ✓ Workshops
- ✓ Environmental Studies

- ✓ Auto Power Off Function Can Be Disabled
- ✓ Battery Life 140 Hours Typical Use
- ✓ °C/°F Switchable

HH68K



HH68K shown smaller than actual size.

HH68K Type K Thermometer with Probe Attached

Specifications

Temperature:

Range: -30 to 850°C (-22 to 1562°F)

type K (CHROMEGA®-ALOMEGA®)

Resolution: 1°C or 1°F, 0.1°C or 0.1°F (Auto)

Accuracy (does not include probe): 18 to 28°C (64 to 83°F) ambient ±(0.3% rdg + 1°C) on °C ranges ±(0.3% rdg + 2°F) on °F ranges

Resolution

0.1°C	-30 to 199.9°C
1°C	200 to 850°C
0.1°F	-22 to 199.9°F
1°F	200 to 1562°F

Range

Dimensions: 160 H x 48 W x 24 mm D (6.3 x 1.9 x .94")

Weight: Approx 80 g (2.8 oz) including battery

Probe: Stainless steel

Probe Diameter: 3.2 mm (1/8") with pointed tip

Probe Length: 132 (5.2")

Display: 3 1/2 digit LCD

Low Battery Indication: The "⚡" is displayed when the battery voltage drops below the operating level

Measurement Rate: 1.5 times/second

Operating Environment: 0 to 50°C (32 to 122°F) <70% RH

Storage Environment: -20 to 60°C (-4 to 140°F), 0 to 80% RH with battery removed from meter

Accuracy: Stated accuracy at 23°C ±5°C (73°F ±9°F), <75% RH

Battery: 1.5V x 3 pcs "AAA" size (not included)

Battery Life: 140 hours (continuity) typical

To Order

Model No.	Description
HH67	Semiconductor thermometer with probe attached
HH68K	Type K thermometer with probe attached
SC-50	Soft carrying case

Comes complete with operator's manual and magnet hanger.

Ordering Example: HH68K, Type K thermometer with probe attached.