

# FLIR H SERIES

TACTICAL THERMAL NIGHT VISION

## SEE AT NIGHT, STAY SAFE

FLIR H-Series set the industry standard for law enforcement thermal imaging cameras and continues to deliver images and video that identifies suspects and keeps officers safe. Being able to see clearly in total darkness enhances mission effectiveness, maximizes operational capabilities, and improves officer safety.

With a variety of lens options and onboard image storage and video capture capabilities, H-Series is a potent thermal imaging package for:

- K-9 operations
- Limited response calls
- Daily patrol
- Reconnaissance & surveillance ops

Now With Interchangeable Lenses




The World's Sixth Sense™

1.888.610.7664

 [www.calcert.com](http://www.calcert.com)

[sales@calcert.com](mailto:sales@calcert.com)





SYSTEM	HS-X 320	HS-X 640
Model	Patrol / Command	
Detector Resolution	320 x 240	640 x 480
Field of View	24° x 18°	7° x 5°
E-Zoom	2X	
Start-up from Standby	<2 seconds	
IMAGE PRESENTATION		
Image Optimization	FLIR proprietary digital detail enhancement	
Refresh Rate	30Hz — 9Hz exportable	
External Video (via RCA jack)	NTSC or PAL composite video	
Polarity	White Hot, Black Hot	
Video/Still Image Storage, SD/SDHC Card-enabled (up to 16Gb)	Command models only	
PHYSICAL		
Weight (w/ battery)	1.45 lb	1.55 lb
Size (LxWxH)	9.36"x3.33"x2.62"	10.96"x3.33"x2.69"
Warranty	1-year Standard; 3/10-year with Registration†	
POWER		
Battery Type	4 Rechargeable AA NiMH batteries (included)	
Battery Life Operating	4-5 Hours Typical (100 + Hours)	
ENVIRONMENTAL		
Ratings	IP-67	
Operational Temp	-4° - 140° (-20°-60°)	

Actual range may vary depending on camera setup, focus adjustment (if available), environmental conditions (i.e., humidity, rain, snow, fog, etc.), user experience, and display method.

†Register camera at [FLIR.com/cs/](http://FLIR.com/cs/) warranty to upgrade to a 3-year Parts & Labor, 10-year detector warranty for free.

LENSES (Purchased Separately)	QD35	QD65	QD100	QD35	QD65	QD100
Size	Ht. - 2.2" Dia - 3.1" Ø	Ht. - 3.3" Dia - 3.1" Ø	Ht. - 4.6" Dia - 3.1" Ø	Ht. - 2.2" Dia - 3.1" Ø	Ht. - 2.2" Dia - 3.1" Ø	Ht. - 2.2" Dia - 3.1" Ø
FOV (320 x 240)	13° x 10°	7° x 5°	5° x 3°	18° x 13°	10° x 8°	6° x 4°
E-Zoom FOV (Resolution):						
2x	6.5° x 5° (160 x 120)	3.5° x 2.5° (160 x 120)	2.5° x 1.5° (160 x 120)	9° x 6.5° (320 x 240)	5° x 4° (320 x 240)	3° x 2° (320 x 240)
4x	N/A	N/A	N/A	4.25° x 3.25° (160 x 120)	2.5° x 2° (160 x 120)	1.5° x 1° (160 x 120)
LENS PACKAGE INCLUDES:	QD35, QD65 or QD100 Lens (as selected at purchase), Lens Cap, Lens Cover, Lens Cloth					
RANGE PERFORMANCE						
Detect Man (1.8 m x 0.5 m)	~850 yds	~1,400 yds	~1.2 mi	~1,200 yds	~1.1 mi	~1.5 mi
Detect Vehicle (4 m x 1.5 m)	~1.3 mi	~2.4 mi	~3.2 mi	~1.5 mi	~2.9 mi	~3.7 mi

Actual range may vary depending on camera setup, focus adjustment (if available), environmental conditions (i.e., humidity, rain, snow, fog, etc.), user experience, and display method.

Note: The thermal images shown are for illustrative purposes only, and may not have been taken by the camera series depicted. Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited.  
©2016 FLIR Systems, Inc. Specifications are subject to change without notice, check our website: [www.flir.com](http://www.flir.com). 01/15/16



HS-X 320

HS-X 640



The World's **Sixth Sense™**

1.888.610.7664

 [www.calcercert.com](http://www.calcercert.com)

[sales@calcercert.com](mailto:sales@calcercert.com)