

IRT227 12:1 Infrared Thermometer with Type K Input

Measures Non-Contact Infrared, Type K, and Air Temperature

Features:

- Instantly measure the temperature of objects without making contact
- Built-in laser identifies the measurement area
- 0.05 to 1.00 adjustable emissivity
- Audible and Visual High/Low Temperature Alarms
- Type K thermocouple input for high temperature measurements
- Min/Max/Avg/Diff
- Backlit LCD display with selectable °F or °C readout
- Automatic Data Hold
- Auto power off after 10 seconds
- Battery capacity indicator
- Optional model complete with Certificate of Traceability to N.I.S.T.
- Includes Type K bead probe and 9V battery
- 1-year warranty

Applications:

- For measuring the surface temperature of solid objects as well as in liquids and ambient temperature

Specifications

| | |
|--------------------------|-----------------------------------|
| IR Temperature Range | -58 to 1112°F (-50 to 600°C) |
| Accuracy | ±3% or 4°F/2°C |
| Resolution | 0.1°F/°C |
| Distance to Target Ratio | 12:1 |
| Response Time | <500ms |
| Emissivity | 0.05 to 1.00 adjustable |
| Laser | Single point |
| Type K Temperature | -58 to 1832°F (-50 to 1000°C) |
| Accuracy | ±(3% + 1.8°F/1°C) |
| Air Temperature | -4 to 158°F (-20 to 70°C) |
| Accuracy | ±3.6°F/2°C |
| Power | 9V battery |
| Dimensions | 6 x 4.7 x 1.7" (153 x 120 x 42mm) |
| Weight | 4.9oz (138g) |



NIST
TRACEABLE
CALIBRATION
AVAILABLE

Ordering Information:

IRT227 12:1 Infrared Thermometer with Type K
IRT227-NIST IRT227 with Certificate of Traceability to N.I.S.T.

