

Part No.

LC20-VF2M-00-00

LC20 pressure gauge, -15 to 30 psi / -100 to 200 kPa, 1/4"
Male NPT bottom connection

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-VF2M-00-00

Specs/Attributes

Battery Count	2
Battery Life	1000 Hours
Battery Type	AA Alkaline (IEC-LR6)
Bluetooth Radio Installed	No
Calibration Certificate	ISO 17025:2017 Accredited
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Panel Mount	No
Primary Power	Battery Power
Process Connection Location	Bottom mount

Specs/Attributes

Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Wireless	None
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Bottom)

Process Connection	1/4" Male NPT
Engineering Units	atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm ² , mmHg @0°C, Torr, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in ²
Burst Pressure	120 PSI / 8.3 bar / 830 kPa
Wrench Size	7/8 In 23 mm
Wetted Materials	316 Stainless Steel
Min Storage Temperature	-40 °F / -40 °C
Max Operating Temperature	120 °F / 50 °C
Max Vacuum	30 InHg / 101.6 kPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Light motor oil, Mineral Oil, Natural Gas, Petroleum Based Oil, Ralston Calibration Oil, Skydrol, Transmission fluid, Water, Windshield washer fluid, Oxygen (If Oxygen cleaned)
Min Operating Temperature	-4 °F / -20 °C
Max Storage Temperature	165 °F / 75 °C
Max Pressure	30 PSI / 2 bar / 200 kPa
Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Sensor Type	Pressure Sensor
Measurement Type	Gauge Pressure
Country of origin	USA