

Part No.

LC30-GC2M-TX125-00

LC30 Pressure / temperature gauge, +/-15 psi pressure, 1/4" Male NP

The LC30 is a robust device that measures and display



LC30-GC2M-TX125-00

Specs/Attributes

Backup Power	AAA Alkaline (IEC-LR03)
Battery Count	2
Battery Life	1000 Hours
Calibration Certificate	NIST traceable (included)
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Datalogging	PC based (via USB)
Electrical Rating	50 mA @ 5 VDC
Harmonized Code	9026.20.0000
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Media Compatibility	Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)
Panel Mount	Yes
Power Input	90-264 VAC, 50-60 Hz
Primary Power	AC Mains Power
Process Connection Location	Back mount

Specs/Attributes

Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)
Temperature Compensation	None
USB Connection	USB (Micro B)
W1 Radio Installed	No
Wetted Materials	316 Stainless Steel
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

Sensor A (Back)

Max Vacuum	-30.00 InHg / -101.6 kPa
Measurement Type	Gauge Pressure, Gauge Vacuum
Accuracy - Pressure Measurement	+/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Engineering Units	atm, bar, cmH2O @4 °C, inH2O @39 °C, kPa, mbar, psi, inHg @39 °F, kgf / cm^2, mmHg @0 °C, Torr, mmH2O @4 °C, ftH2O @39 °F, cmHg @ 0 °C, oz / in^2
Wrench Size	7/8 In 23 mm
Sensor Type	Pressure Sensor
Max Storage Temperature	165 °F / 75 °C
Min Storage Temperature	-40 °F / -40 °C
Country of origin	USA
Max Pressure	15 PSI / 1 bar / 100 kPa
Wetted Materials	316 Stainless Steel
Max Operating Temperature	120 °F / 50 °C
Min Operating Temperature	-4 °F / -20 °C
Process Connection	1/4" Male NPT

Sensor B (Back)

Max Probe Temperature	300 °F / 150 °C
Min Probe Temperature	-22 °F / -30 °C
Thermal Probe	1/4 in / 6.35 mm diameter, 12 in / 30.5 cm long, external cable, 20 ft / 6.1 m long
Wetted Materials	316 Stainless Steel
Measurement Type	Temperature
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water



Sensor B (Back)

Accuracy - Temperature Measurement	$\pm (0.15 + 0.002 \cdot t)$ °C (IEC 60751 Class A)
Country of origin	USA
Electrical Connection	M12 female, A Code, Silicone seal, IP67
Temperature Units	°C, °F, K, R