

Part No.

# LC30-GR2M-GJ2M-00

*LC30 panel mount dual sensor pressure gauge, 3000 psi back, 100 psi back connection, both 1/4" Male NPT*

The LC30 is a robust device that measures and displays pressure readings on a large, backlit screen. It is AC powered with a battery backup. The LC30 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and logging pressure.



LC30-GR2M-GJ2M-00

## Specs/Attributes

|                           |                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Backup Power              | AAA Alkaline (IEC-LR03)                                                                                                                                                                                              |
| Battery Count             | 2                                                                                                                                                                                                                    |
| Battery Life              | 1000 Hours                                                                                                                                                                                                           |
| Burst Pressure            | 12000 PSI / 825 bar / 83 MPa                                                                                                                                                                                         |
| Calibration Certificate   | NIST traceable (included)                                                                                                                                                                                            |
| Certifications            | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Country of origin         | USA                                                                                                                                                                                                                  |
| Datalogging               | PC based (via USB)                                                                                                                                                                                                   |
| Electrical Rating         | 50 mA @ 5 VDC                                                                                                                                                                                                        |
| Harmonized Code           | 9026.20.0000                                                                                                                                                                                                         |
| Ingress Protection        | IP67 (1 meter water submersion for 30 minutes)                                                                                                                                                                       |
| LCD Display               | 2.4 in / 61 mm segmented LCD Display                                                                                                                                                                                 |
| Materials                 | ABS / Polycarbonate Blend, Powder Coated Aluminum                                                                                                                                                                    |
| Max Operating Temperature | 120 °F / 50 °C                                                                                                                                                                                                       |
| Max Pressure              | 3000 PSI / 200 bar / 20 MPa                                                                                                                                                                                          |
| Media Compatibility       | Inert Gas, Natural Gas, Petroleum Based Oil, Water                                                                                                                                                                   |
| Min Operating Temperature | -4 °F / -20 °C                                                                                                                                                                                                       |
| Operating Altitude (max)  | 10,000 ft (3050 m)                                                                                                                                                                                                   |
| Panel Mount               | Yes                                                                                                                                                                                                                  |
| Power Input               | 90-264 VAC, 50-60 Hz                                                                                                                                                                                                 |
| Primary Power             | AC Mains Power                                                                                                                                                                                                       |

## Specs/Attributes

|                             |                                                                   |
|-----------------------------|-------------------------------------------------------------------|
| Process Connection Location | Back mount                                                        |
| Protection Class            | Pollution Degree 2 (UL / IEC 61010-1)                             |
| Relative Humidity           | 0% to 90% (-10 to 35 °C) , 0% to 70% (35 to 50 °C)                |
| Temperature Compensation    | None                                                              |
| USB Connection              | USB (Micro B)                                                     |
| W1 Radio Installed          | No                                                                |
| Wetted Materials            | 316 Stainless Steel                                               |
| Connector End 1             | 1/4" Male NPT (ASME B1.20.1)                                      |
| Weight                      | 12.6 oz / 355 grams                                               |
| Dimensions                  | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm) |

## Sensor A ( Back)

|                                 |                                                                                                                                                                                                                           |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max Operating Temperature       | 120 °F / 50 °C                                                                                                                                                                                                            |
| Min Operating Temperature       | -4 °F / -20 °C                                                                                                                                                                                                            |
| Process Connection              | 1/4" Male NPT                                                                                                                                                                                                             |
| Sensor Type                     | Pressure Sensor                                                                                                                                                                                                           |
| Wrench Size                     | 7/8 In<br>23 mm                                                                                                                                                                                                           |
| Engineering Units               | atm, bar, inH2O @39°C, kPa, MPa, psi, inHg @39°F, kgf / cm^2, Torr, ftH2O @39°F, cmHg @ 0°C, oz / in^2                                                                                                                    |
| Max Storage Temperature         | 165 °F / 75 °C                                                                                                                                                                                                            |
| Min Storage Temperature         | -40 °F / -40 °C                                                                                                                                                                                                           |
| Measurement Type                | Gauge Pressure                                                                                                                                                                                                            |
| Max Pressure                    | 3000 PSI / 200 bar / 20 MPa                                                                                                                                                                                               |
| Wetted Materials                | 316 Stainless Steel                                                                                                                                                                                                       |
| Country of origin               | USA                                                                                                                                                                                                                       |
| Burst Pressure                  | 12000 PSI / 825 bar / 83 MPa                                                                                                                                                                                              |
| Media Compatibility             | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)                                                                                                                                                              |

## Sensor B (Back)

|                         |                             |
|-------------------------|-----------------------------|
| Max Storage Temperature | 165 °F / 75 °C              |
| Min Storage Temperature | -40 °F / -40 °C             |
| Burst Pressure          | 400 PSI / 28 bar / 2.80 MPa |

## Sensor B (Back)

|                                 |                                                                                                                                                                                                                           |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max Operating Temperature       | 120 °F / 50 °C                                                                                                                                                                                                            |
| Min Operating Temperature       | -4 °F / -20 °C                                                                                                                                                                                                            |
| Process Connection              | 1/4" Male NPT                                                                                                                                                                                                             |
| Media Compatibility             | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1)                                                                                                                                                              |
| Engineering Units               | atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Torr, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in^2                                                                           |
| Country of origin               | USA                                                                                                                                                                                                                       |
| Measurement Type                | Gauge Pressure                                                                                                                                                                                                            |
| Max Pressure                    | 100 PSI / 7 bar / 700 kPa                                                                                                                                                                                                 |
| Wetted Materials                | 316 Stainless Steel                                                                                                                                                                                                       |
| Sensor Type                     | Pressure Sensor                                                                                                                                                                                                           |
| Wrench Size                     | 7/8 In<br>23 mm                                                                                                                                                                                                           |