

# LT300

## High current loop testers



- High current loop tester
- Single and 3 phase testing
- 16 Hz to 400 Hz operation
- CATIV 300 V applications
- Two wire lead set or mains plug leads
- Tough armoured case

### DESCRIPTION

The LT300 offers high current loop testing over a wide range of frequencies and supply voltages with simple, fast, two wire operation.

It has a large clear display that aids visibility in poor conditions.

#### Two models are available:

LT300-EN-00 - with red/green leads

LT300-EN-BS - with BS1363 mains plug lead

LT300-EN-FS - with fused red/green leads

The high current loop test provides fast accurate and stable results with a resolution to 0.01  $\Omega$  on the 20  $\Omega$  range.

#### Frequency range

Supply frequency is indicated upon connection to the supply. This will automatically set to the measured supply frequency either 16 Hz, 50/60 Hz or 400 Hz. Testing will commence automatically.

#### Loop Impedance measurement:

Two loop impedance ranges are provided.

20  $\Omega$  - Resolution to 0.01  $\Omega$

200  $\Omega$  - Resolution to 0.1  $\Omega$

#### Supply voltage:

Operational supply range extends from 50 V to 550 V (400 V @ 16 Hz), with a warning for voltages over 330 V highlighting accidental phase to phase connections on a nominal 230 V system.

Single Phase CATIV 300 V phase to earth, as well as 550 V phase to phase applications (400 V @ 16 Hz)

#### GENERAL 1

The instrument is housed in a rubber armoured case with a built-in cover to protect the display when not in use.

The IP54 weatherproof rating provides excellent protection in adverse conditions.

The instrument is supplied with either a two wire (red/green) lead set, or a mains plug test lead for access to wall sockets, a certificate of test and a hard carry case.

### SPECIFICATION

#### Voltage measurement range

**Voltage range:** 0 V to 550 V (400 V @ 16 Hz)

**Accuracy:** ±5% ±2 V

#### Loop test operating frequencies

16 Hz            15 Hz to 18 Hz, 33 Hz, 29 Hz to 337 Hz

50/60 Hz        40 Hz to 70 Hz, 125 Hz, 100 Hz to 142 Hz

400 Hz          260 Hz to 498 Hz

#### Test currents

20 ½ Range    200 ½ Range

550 V            27 A            2.7 A

230 V            12 A            1.2 A

115 V            6 A             0.6 A

50 V             3 A             0.3 A

#### Loop test accuracy

##### Loop resistance:

0 to 19.99 ½ (20 ½ range) ±5% ±0.03 ½

0 to 199.9 ½ (200 ½ range) ±5% ±0.5 ½

#### Environmental

**Operating temperature:** -10°C to +60°C

**Storage temperature:** -25°C to +70°C

**Humidity:** 90%RH @+40°C

**Maximum altitude:** :2,000 m

**Dust and water:** IP54

**Battery:** 8 x AA (LR6) alkaline or NiMH rechargeable cells.

#### Safety

Meets the requirements of IEC61010-1 300 V CATIV phase to earth or 550 V Phase to Phase (400 V @ 16 Hz).

#### EN61557

Complies with the following parts of EN61557, Electrical safety in low voltage systems up to 1000 V a.c. and 1500 V d.c. Equipment for testing, measuring or monitoring of protective measures:

Part1 - General Requirements

Part3 - Loop resistance

#### EMC

In accordance with IEC61326-1

**Weight:** 980gms (2.16lb)

**Dimensions:** 203 x 148 x 78mm ( 8 x 5.8 x 3 in)



**ORDERING INFORMATION**

Description	Order Code
High current loop tester with red/green lead set	LT300-EN-00
High current loop tester with BS1363 mains plug lead	LT300-EN-BS
High current loop tester complete with fused leads	LT300-EN-FS
Included Accessories	
Red/green 2 wire test lead set (LT300-EN-00)	1001-976
Mains plug test lead (BS1363) (LT300-EN-BS)	6220-810
Hard carry case	5410-409
Fused leads ONLY WITH LT300-EN-FS	1001-977
<b>Optional Accessories</b>	
Mains plug test lead (BS1363) (LT300-EN-BS)	6220-810
Red/green 2 wire test lead set (LT300-EN-00)	1001-976
Spare fuse for leads	25950-013