

**GENERAL®**

# Pin-type LED Bar Graph Moisture Meter



**Ideal for use in woodworking, building construction and home inspection**

**Examples include:**

- Checking for moisture in carpets and sub-flooring
- Checking wood, drywall and concrete before painting/wallpapering, sealing or treating
- Locating water leaks in roofs, floors and walls
- Selecting dry lumber

## Features

- 10-LED display
- 7 to 35% measurement range, w/separate High and Low scales
- Protective cap doubles as calibration checker
- Replaceable pins
- Full and low battery indications

## Specifications:

### Low Measurement Range:

7 to 15% WME (Wood Moisture Equivalent)

### High Measurement Range: 16 to 35% WME

Measurement Accuracy:  $\pm 1$  LED (~1%)

Calibration Check Point: 21%  $\pm 2\%$

Low Battery Level:  $< 7.5V$

Current Consumption:  $< 15mA$

### Operating Temperature:

32° to 140°F (0° to 60°C)

### Storage Temperature:

23° to 140°F (-5° to 60°C)

### Dimensions:

6.5 x 2.7 x 1 in. (164 x 69 x 26mm)

Weight: 3.2 oz. (91g)

Power Source: 1 "9V" battery (included)

## Includes:

Protective Cap, Battery and User's Manual



No. MM1E



Drywall

**GENERAL®**