KLEIN TOOLS

DIGITAL
MULTIMETERS

MM700	MM600	MM400	MM300
• Auto-ranging • True root mean square (TRMS) • 10A AC/DC current • AC/DC Voltage • Resistance • Continuity • Frequency • Duty cycle • Capacitance • Tests diodes • Temperature • Low Impedance (LoZ) mode	• Auto-ranging • 10A AC/DC current • AC/DC Voltage • Resistance • Continuity • Frequency • Duty cycle • Capacitance • Tests diodes • Temperature	• Auto-ranging • 10A AC/DC current • AC/DC Voltage • Resistance • Continuity • Frequency • Duty cycle • Capacitance • Tests diodes • Temperature	• Manual-ranging • 10A AC current • AC/DC Voltage • Resistance • Continuity • Tests diodes
• Instruction Manual • Test Leads with CATIII/CAT IV safety caps • Thermocouple with adapter • Alligator Clips • 2 x AAA Batteries • Carrying Case	• Instruction Manual • Test Leads with CATIII/CAT IV safety caps • Thermocouple with adapter • Alligator Clips • 2 x AAA Batteries • Carrying Case	• Instruction Manual • Test Leads with CATIII/CAT IV safety caps • Thermocouple with adapter • 2 x AAA Batteries	• Instruction Manual • Test Leads with CATIII/CAT IV safety caps • 2 x AAA Batteries
CATIV 600V, CATIII 1000V CE	CATIV 600V, CATIII 1000V CE	CAT III 600V, CE	CAT III 600V, CE
7.00" (177.8 mm)	7.00" (177.8 mm)	6.00" (152.4 mm)	6.00" (152.4 mm)
3.55" (90.1 mm)	3.55" (90.1 mm)	3.16" (80.4 mm)	3.16" (80.4 mm)
2.09" (53.2 mm)	2.09" (53.2 mm)	1.78" (45.2 mm)	1.78" (45.2 mm)
0.90 lb (0.41 kg)	0.90 lb (0.41 kg)	0.51 lb (0.23 kg)	0.51 lb (0.23 kg)

Includes / Standards / Overall Length / Overall Width / Overall Depth / Weight

FEATURES	MM700	MM600	MM400	MM300
Drop Protection	6.6' (2 m)	6.6' (2 m)	3.3' (1 m)	3.3' (1 m)
Ingress Protection	IP42	IP42	–	–
Safety	CAT IV 600V CAT III 1000V	CAT IV 600V CAT III 1000V	CAT III 600V	CAT III 600V
AC Voltage (Volts)	1000V	1000V	600V	600V
DC Voltage (Volts)	1000V	1000V	600V	600V
AC Current (Amps)	10A	10A	10A	10A
DC Current (Amps)	10A	10A	10A	–
Ohms (Resistance)	40MΩ	40MΩ	40MΩ	2MΩ
DC Millivolts	●	●	●	●
AC Milliamps	●	●	●	–
DC Milliamps	●	●	●	●
AC Microamps	●	●	●	–
DC Microamps	●	●	●	●
True RMS	●	–	–	–
Audible Continuity	●	●	●	●
Backlight	●	●	●	–
Temperature	0° – 1500°F (-18° – 816°C)	0° – 1000°F (-18° – 538°C)	0° – 1000°F (-18° – 538°C)	–
Low Impedance	●	–	–	–
Auto Ranging	●	●	●	–
Range Hold	●	●	●	–
Data Hold	●	●	●	●
Diode Test	●	●	●	●
Capacitance Test	4000 µF	1000 µF	200 µF	–
Frequency / Duty Cycle	1Hz – 500 KHz	1Hz – 500 KHz	1Hz – 50 KHz	–
Max / Min	●	●	●	–
Lead Warning	●	●	–	–
Bar Graph	●	–	–	–
Magnetic Mount	Available As Accessory	Available As Accessory	Available As Accessory	Available As Accessory
Auto-Power Off	●	●	●	–
Battery Test	–	–	–	●
LCD Display Count	4000	4000	4000	2000

Specifications subject to change

1.888.610.7664 www.calcert.com sales@calcert.com