



Universal Process Indicator

N1500



DESIGNED FOR
HIGH-RESOLUTION
VIEWING



- High responsiveness to process variable
- Allows visual acuity at a distance
- Timer function for safety alarms
- 30-point linearization for non-standard sensors



N1500 universal process indicator works at fast sampling rate, which ensures high-performance indication and reaction to fast processes dynamics. With 6 digits for high-resolution variables and the 17mm height display, N1500 provides clear view, making it easier for operators to read and diagnose from a distance.

Its timer function performs wide action capabilities through

alarms for safety interlock logic. Furthermore, N1500 is fully compatible with custom signals through its linearized input for up to 30 points.

Both electronic robustness and anti-flame material enclosure comply with the main world-class approvals for industry devices.

novus
We Measure. We Control. We Record.

1.888.610.7664



www.calcert.com

sales@calcert.com



Display	7-segment LED, 6-digit with 17 mm height	Auxiliary Power Supply	24 Vcc
Input Type	Thermocouples J, K, T, N, R, S, B, E, Pt100, 0-20 mA, 4-20 mA, 0 -50 mV, 0-5 Vdc, 0-10 Vdc, 4-20 mA no linear, 0-20 mA custom linear, 4-20 mA custom linear, 0-20 mA custom no linear, 4-20 mA custom no linear	Optional	2 relays, analog output (4-20 mA or 0-20 mA), RS485
Accuracy	Thermocouples J, K, T: 0.25% of span $\pm 1^{\circ}\text{C}$ Thermocouples N, R, S, B: 0.25% of span $\pm 3^{\circ}\text{C}$ Pt100, 0-20 mA, 4-20 mA, 0-5 Vdc, 0-10 Vdc: 0.2% of the span	Communication	RS485 Modbus RTU optional
Sampling Rate	5 samples per second for Pt100 and Thermocouples 15 samples per second for 0-50 mV, 4-20 mA, 0-5 V and 0-10 V	Math Function	Square Root
Display Resolution	Temperature: 1 / 0.1 Other measures: 1 / 0.1 / 0.01 / 0.001 / 0.0001	Safety	Password protected configuration
Custom Linearization	30 points for non-standard sensors	Configuration Interface	Via RS485
Digital Input	Operates as a key for Hold, Peak Hold and maximum/minimum reset	Power Supply	100-240 Vac / dc or 12-24 Vdc
Analog Output	0-20 mA or 4-20 mA (optional) - electrically isolated	Maximum Consumption	7.5 VA
Alarms	Up to 4 alarms	Dimensions	96 x 48 x 92 mm (1/8 DIN)
Alarm Types	Minimum, maximum, minimum differential, maximum differential, differential out of range, differential within range, and open sensor	Front Panel	IP65 Polycarbonate (PC) UL94 V-2
Timer Function	Alarms with delay, pulse or oscillator timing	Enclosure	IP30 ABS + PC UL94 V-0
		Operating Conditions	5 to 50 $^{\circ}\text{C}$, and 0 to 80% RH up to 30 $^{\circ}\text{C}$
		Aprovals	CE, UL and cUL