



Empowering you to work smarter

NSTL

Large Bluetooth Temperature Clamp with Digital Display



Compatible with *myNAVAC™* App




**A2L
Compatible**

4-1/8" Opening



Large Digital Display



Large Opening

Precision Temperature Measurement

Large Opening

- 3/4" to 4-1/8" opening
- For residential, commercial and refrigeration applications

Accuracy and Fast Response

- High accuracy thermoelectric sensor
- Large contact surface

Large Digital Display

- Standalone use as a digital thermometer
- Works with or without myNAVAC™ App
- Quick response with real-time display

Durability and Convenience

- Robust design, IP54 rating for dust and water resistance
- 2 x AAA battery included, up to 150 hours battery life
- Optional auto power-off after 2 hours

Bluetooth Connectivity

- Works wirelessly with myNAVAC™ App
- Works wirelessly with NEXUS Manifold Gauge

Universal Temperature Clamp

- Suitable for either High (HP) or Low (LP) Side

Model	NSTL
Measurement Range	-40~257°F (-40~125°C)
Accuracy	±2.7°F (±1.5°C)
Resolution	0.1°F
Sensor Type	Thermocouple (Nickel Chromium)
Pipe Size Compatibility	3/4" ~ 4-1/8" OD
Refresh Rate	1 time/second
Bluetooth Range	164' (50m)
Battery Type	2 x AAA
Battery Operating Time	Screen off: >150h; Screen on: >12h
Certification	CE, FCC, RoHS
Wireless Frequency	2.4 GHz
Minimum Device Requirement	BLE4.0 or above, Android 7.0.0 or above, Apple iOS 12.0 or above
Water Resistance	IP54
Unit Weight	7.8 oz
Accessory	Carry bag

1-YEAR WARRANTY

1.888.610.7664



www.calcert.com

sales@calcert.com