



Empowering you to work smarter



Compatible with myNAVAC™ App  
& measureQuick® App

# NX4G NX4GV NEXUS 2 Digital Manifold Gauge

PATENT PENDING

# 4 Valve



## Touch • Read • Master

### Powerful Visual w/ HD Color Interface

- Choose your work style from four themes: Classic, America, Galaxy, Daylight
- Convert data into visuals with enhanced UI
- Self-explanatory interface
- Highly responsive 5.5" touch screen

### Rugged and Reliable

- Shock-absorbing corner protection
- Heavy-duty shell & aluminum body
- IP54 rated for harsh conditions

### Precision, Smart and Wireless

- Class 0.4 accuracy with digital display
- Bluetooth connections with temp clamps & micron gauge
- Work with myNAVAC App & MeasureQuick
- Supports over 100 refrigerants, updatable via App

### Ease of Use

- 1/4 turn ball valves & swivel ports
- Rechargeable lithium battery w/ quick charge
- Adjustable brightness

### Multiple Operation Modes

- Manifold Gauge mode with SH/SC display
- Leak Test mode
- Evacuation mode with decay test function
- Touchscreen navigation for faster operation

### Portability

- Multi-purpose carry case
- Folding hook for portability
- Extension canvas hook

| Model                     | NX4G (Vacuum Gauge Not Included)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | NX4GV (Vacuum Gauge Included)                  |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Refrigerant Type          | R11, R113, R114, R115, R116, R12, R1224yd(Z), R123, R1233zd, R1233zd(E), R1234yf, R1234ze, R1234ze(E), R1234ze(Z), R124, R1243zf, R125, R13, R134a, R1409A, R22, R23, R236fa, R245fa, R290, R32, R401A, R401B, R401C, R402A, R402B, R403A, R403B, R404A, R405A, R406A, R407A, R407B, R407C, R407D, R408A, R41, R410A, R410B, R411A, R411B, R412A, R413A, R414A, R414B, R415A, R415B, R416A, R417A, R417C, R420A, R421A, R421B, R422A, R422B, R422C, R422D, R424A, R427A, R428A, R434A, R437A, R438A, R447A, R447B, R448A, R449A, R450A, R451A, R451B, R452A, R452B, R452C, R453A, R454A, R454B, R454C, R455A, R456A, R458A, R459A, R459B, R460A, R460B, R500, R501, R502, R503, R507A, R508B, R513A, R600, R600a, R601, R601A<br>Firmware can be updated at NAVAC website or with MyNAVAC™ App |                                                |
| Screen Configuration      | IPS touch screen, 1024 x 512 pixel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                |
| Ports                     | (1) 3/8" sae for evacuation; (3) 1/4" sae for suction line, liquid line, and refrigerant recovery/charging                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                |
| Maximum Manifold Pressure | 1087 psi (7500 kPa)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                |
| Bluetooth Range           | 260 ft (80m) line of sight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                |
| Power Supply              | Rechargeable 3000mAh lithium battery, 8~100 hours run time, Type-C charging port                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                |
| Language                  | English, Spanish, French                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                |
| Accessory                 | Bluetooth Temperature Clamps NST1 (Low Side), NST2 (High Side), Charging Cable, Storage Bag                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | NMV1S Vacuum Gauge in addition to the NX4G Kit |

2-YEAR WARRANTY

1.888.610.7664



www.calcert.com

sales@calcert.com