

# DIAGONAL PLIERS

## ***Diagonal Pliers*** **Feature:**



- Box joint
- Designed for general wire cutting, flush cutting, or in confined spaces
- Heat treated edges — for longer cutting edge life
- Polished head

### **SPECIFICATIONS**

|                        | P4D    | P6D    | P7D    | P8D    |
|------------------------|--------|--------|--------|--------|
| <b>Overall Length</b>  | 4.00"  | 6.00"  | 7.00"  | 8.00"  |
| <b>Jaw Length</b>      | .44"   | .81"   | 1.00"  | .79"   |
| <b>Joint Thickness</b> | .44"   | .44"   | .49"   | .43"   |
| <b>Joint Width</b>     | .44"   | .75"   | .94"   | 1.18"  |
| <b>Weight</b>          | .45 lb | .50 lb | .52 lb | .66 lb |

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC when working on live parts
- Made in the U.S.A.
- Marked with the international safety symbol –  1000V