



Model PC-620 Ultrasonic Pipette Cleaner

OVERVIEW

PC-620 Branson® benchtop units are designed to ultrasonically clean pipettes and other tubular glassware. Lipids, blood, and proteins are easily removed from the capillary bore of the pipette through the cavitation process. Useful in medical and scientific laboratories, the ultrasonic pipette cleaner is available in both heated and unheated versions.

An optional stainless steel cover is available. A pipette basket is recommended, as parts should not rest on bottom of tank. The basket holds the pipettes inside the ultrasonic tank.

COMPLETE INTEGRATED UNIT

The Model PC-620 has a 2-3/4 gallon capacity cleaning tank and ultrasonic generator enclosed in a sheet metal housing. The stainless steel tank has no corner welds or other dirt catch-

ing surfaces, and is provided with a bottom mounted drain. Circuitry is solid state for long trouble-free service. High efficiency industrial piezoelectric transducers are attached to the tank bottom and operate at 40 kHz..

CLEANING APPLICATIONS

The Model PC-620 is not only designed for pipette cleaning. Its unique size makes it ideal for large and odd-size parts that conventional cleaners cannot handle. The many uses of this model include cleaning metal and plastic machine parts, electrical and electronic components, as well as mixing and degassing chemical solutions. Branson also offers a variety of cleaning chemistries suitable for your particular cleaning needs.



EMERSON
Industrial Automation



Precision Cleaning

SPECIFICATIONS

PC620R-1 Unheated

Part Number 000-951-030 (115 volts)

PC620R-2 Heated

Part Number 000-951-330 (115 Volts)

PC620E-1 Unheated

Part Number 000-951-130 (230 Volts)

PC620E-2 Heated

Part Number 000-951-430 (230 Volts)

Stainless Steel Basket

Part Number CPN-916-033

Stainless Steel Cover

Part Number 000-410-105

Tank Dimensions: 19-1/2"L x 5-3/4"W x 6"D (495 mm x 133 mm x 152 mm)

External Dimensions: 20-1/4"L x 6-1/4" W x 10-1/2"D
(521 mm x 159 mm x 267 mm)

Power Requirements: 115 Volts, single phase, 60 Hz,
or 230 Volts, single phase, 50/60 Hz

Capacity: 2-3/4 gallon (8.5 liters)

Shipping weight: 23 lbs. (10.4 kg)

Note: Basket and cover sold separately – cannot place items on tank bottom.

CERTIFICATIONS AND APPROVALS

The unit is equipped with an RFI filter to meet FCC radio frequency interference standards, and is UL and CSA listed.

Branson is ISO 9001 and ISO 14000 certified.

BRANSON

PC-620 © Branson Ultrasonics Corporation 2011
The Emerson logo is a trademark and service mark of Emerson Electric Co.
Revised and printed in the U.S.A. 10/2011

1.888.610.7664



www.calcert.com

sales@calcert.com