

Professional crane scale | industrial environment



Features

- Metal housing
- For industrial environment
- Large LED display, backlit
- With remote control
- Hold function, Peak function, Auto-off function
- Stainless steel shackle (upper suspension) and hook (lower suspension)
- Measuring units changeable (kg, N)
- Integrated, researchable batteries
- Mains adapter for CH/EU included
- Can be calibrated by user

Models				
Item No.	Capacity	Min. load	Division	Official calibration
PCS0500	500kg	4kg	200g	Not legal for trade
PCS1000	1000kg	10kg	500g	Not legal for trade
Design				
Material platform		Aluminum die casting		
Color		Grey		
Outer measurements (without		205x132x125mm		
suspension)				
Net weight / gross weight		4250g / 5300g		
Technical data				
Display		LED, 157x41mm		
Weighing units		Kilogram, Newton		
Calibration		Can be calibrated by user		
Conformity		CE, RoHS		
Power supply		Integrated, researchable battery with approx. 50 hours running time		
		(when using the backlit LED display. CH/EU mains adapter included.		
Operating temperature		0° - 40°C / 32° - 104°F		
Data interface		Non		
Manual		German, French, English		
Scope of delivery		Suspension shackle (upper suspension) and hook (lower suspension),		
		mains adapter for CH/EU		