

PULSER GROUND FAULT LOCATOR

TESTING | TROUBLESHOOTING | ACCURACY

Product Features:

The Pulser Ground Fault Locator identifies the exact location of even the smallest breaks in insulation by “pulsing” a high-voltage signal that radiates into the earth at the location of the faults. With the A-frame mounted receiver, a visual analog meter points the way to the source of the voltage.

- Multiple faults on a single wire can be identified indicating the need to replace instead of repair.
- Extra-long test leads feature heavy-duty alligator clips for use on multiple cable types.
- Includes a rechargeable transmitter, receiver, A-frame, ground stake, 120V charger and a 12V DC (cigarette lighter) adapter.
- Battery operated (one 12V and one 9V battery included).

Ordering Information:

| CAT. NO. | DESCRIPTION |
|----------|---|
| PE2003 | Pulser Fault Locator Kit with carrying case |
| 2000H | Transmitter (Includes CH1 & CH2) |
| 2000R | Receiver |
| AF2 | A-Frame |
| CH1 | AC Charger |
| CH2 | DC Charger |
| 59F0002 | Battery, Replacement (12V 2.5 Ah) |

Specifications:

| | |
|---------------------|--|
| Power Requirements: | Transmitter: (1) 12V rechargeable battery, Receiver: (1) 9V battery |
| Battery Life: | Transmitter: 23 hours per charge Receiver: 200 hours |
| Transmitter Power: | 2400VDC peak |
| Voltage Protection: | 240V ac / 400V dc |
| Construction: | Transmitter: aluminum housing in polyethylene case, Receiver: powder coated aluminum |
| Dimensions: | Transmitter: 17 in x 8.5 in x 6.5 in (421 mm x 215 mm x 160 mm) Receiver: 33.5 in x 21.75 in x 3.25 in (840 mm x 550 mm x 8 mm) |
| Weight: | 12.5 lb complete (5.7 kg) |



Renewed Vision. Innovation Forward.



Follow us on Social Media
@TempoComm

1.888.610.7664

 www.calcert.com

sales@calcert.com