

LevelPro® — PLA

Float Level Switch Assembly & Alarm Light

ICON™ Corrosion-Free
PROCESS CONTROLS Instrumentation Equipment™

Features

- ✓ 6" - 96" Range
- ✓ Up to 2 Relay Contacts
- ✓ Visual Alarm Indication Light
- ✓ 2" NPT Connection
- ✓ PVC | PP | PVDF | 316 SS
- ✓ Superior Chemical Resistance
- ✓ Suitable for Non-Coating Acids | Bases
- ✓ NEMA 4X Enclosure

Precision Liquid Level Detection for Industrial Excellence

The PLA Liquid Level Float Switch provides liquid level detection up to 8' (2.4m) with 1 or 2 level switch points and a compact junction box for wiring termination. Additionally, the PLA features a visual alarm light for upset conditions.

This all plastic level switch package is selected for day tank, skid or machine, cooling tower, waste sump or process tank applications, and can be connected directly to a PLC or relay controller. It makes a perfect on | off switch for pumps or valves and can be used to completely automate your tank. The PLA is only suitable for non-viscous and non-coating liquids.

Visual Alarm Indication Light

Conditions Within Parameters



Upset Condition



M12 Quick
Connection

NEMA 4X

2" NPT

Up to 2
Switching
Points

• PVC
• PP
• PVDF
• 316 SS

PVC

PP

PVDF

316SS



CE



LevelPro® — PLA

Float Level Switch Assembly & Alarm Light



Specifications

General		
Operating Range	0.5 to 8 ft	0.15 to 2.4 m
Connection	2" NPT	
Accuracy	±2 mm	
Hysteresis	8 mm	
Materials		
Sensor Body	PVC PP PVDF 316 SS	
O-Rings	N/A	
Enclosure	Glass Filled Polypropylene NEMA 4X IP67	
Electrical		
Power Supply	24VDC	
Voltage Rating	Minimum Switching Capacity 60VAC 9VDC	Maximum Switching Capacity 120VAC 36VDC
Operating Temperature		
PVC	32°F to 140°F	0°C to 60°C
PP	-4°F to 190°F	-20°C to 88°C
PVDF	-40°F to 240°F	-40°C to 115°C
316 SS	-40°F to 300°F	-40°C to 149°C
Standards and Approvals		
CE FCC RoHS Compliant		

Model Selection

PLA - 2 - 2 - 1 - ?? - 1 - ??

Material | # of Contact Points | Switching Position (SP1) | Length (L1) | SP2 | L2

2: PVC 3: PP 5: PVDF 8: 316 SS	1 2	1: NO 2: NC	Length in inches	1: NO 2: NC	??"
---	-------	----------------	------------------	----------------	-----

PLA — Liquid Level Float Assembly Alarm		
Size	Part Number	Material
6"-24"	PLA-2-X-Y-D	PVC
6"-24"	PLA-3-X-Y-D	PP
6"-24"	PLA-5-X-Y-D	PVDF
6"-24"	PLA-8-X-Y-D	316 SS

Add Suffix -
'X' = # of Floats (1 or 2)
'Y' = NO Contact or NC Contact
'D' = Dimension in Inches

