

## HEAVY-DUTY REPAIRABLE STAINLESS GAUGE


REOTEMP's Series PR gauge offers rugged, all-welded stainless steel construction ideal for heavy-duty industrial applications. The stainless steel case, tube and socket are welded together for superior case sealing and gauge integrity. The twist-off bayonet ring offers easy access for field repair and calibration services. Liquid filling (at the factory or in the field) is recommended for applications involving vibration. For high-corrosive, high-temp, or severe service applications, a diaphragm seal is recommended.



PR40




PR60




PR40

\*dimensions in inches




PR60

\*dimensions in inches



PR40 Mounting Flange



PR60 Mounting Flange



Fillable



Dials



Accuracy



Custom Logo



Diaphragm Seal  
Compatible

### FEATURES / BENEFITS

- All-Welded Stainless Steel Construction
- Removable Bayonet Ring, Micro Adjustable Pointer
- Field Fillable Case, NEMA 4X/IP65
- Internal Overload and Underload Stops, Floating Zero
- Safety Blow-Out Relief



### SPECIFICATIONS

|                                           |                                                                                                                                         |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Accuracy</b>                           | 1%, ASME Grade 1A (10K to 20K ; 2% Upscale, 4% Downscale)                                                                               |
| <b>Ambient Limits</b>                     | -40°F/150°F                                                                                                                             |
| <b>Process Limits</b>                     | -40°F/250°F                                                                                                                             |
| <b>Process Limits with Diaphragm Seal</b> | -60°F/400°F (Direct Mount)*<br>-110°F/750°F (Remote Mount or Cooling Tower)*<br>*Exact limits depend on diaphragm seal and fill fluids. |
| <b>Wetted Materials</b>                   | Tube: 316SS Seamless<br>Socket: 316SS                                                                                                   |
| <b>Lens</b>                               | Tempered Safety Glass , Plastic or Laminated Safety Glass                                                                               |
| <b>Other Materials</b>                    | Case: 304SS<br>Ring: 304SS Twist-Off Bayonet<br>Dial: White Aluminum with Black Letters<br>Case-Socket: Welded                          |
| <b>Fillable</b>                           | Yes                                                                                                                                     |
| <b>Restrictor Screw</b>                   | Yes, removable.                                                                                                                         |
| <b>Maximum Working Pressure</b>           | Stable = 100%<br>Momentary = 130% of scale                                                                                              |
| <b>Environmental Protection</b>           | NEMA 4X/IP65                                                                                                                            |
| <b>Weight</b>                             | 4" = 1.3 lbs (2.0 lbs filled), 6" = 2.1 lbs (4.2 lbs filled)                                                                            |

## HEAVY-DUTY REPAIRABLE STAINLESS GAUGE



- ✓ Check Stock
- ✓ Get Price
- ✓ Configure Part #
- ✓ Download PDF Data Sheets

**HOW TO ORDER:** Choose options to build a part number. For example: **PR40S1A4P01-D-T-HV**

| PR40                   | S                       | 1                       | A                                                                                                                                                     | 4                                                                              | P01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | -D                                                                                                                         | -T                                                                                                   | -HV                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DIAL SIZE              | CASE TYPE               | TUBE & SOCKET           | MOUNT TYPE                                                                                                                                            | CONNECTION                                                                     | RANGE CODE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | CASE FILL                                                                                                                  | LENS                                                                                                 | OPTIONS                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| PR40 = 4"<br>PR60 = 6" | S = 304SS<br>*T = 316SS | 1 = 316SS<br>*3 = Monel | A =  Bottom<br>B =  Bottom/Rear Flange<br>C =  Lower Back<br>D =  Lower Back "U" Clamp<br>E =  Lower Back/Front Flange<br>F =  Lower Back/Rear Flange | 4 = 1/4" NPT<br>2 = 1/2" NPT<br>5 = 1/4" Female High Pressure (9/16" - 18 UNF) | <b>Common Ranges</b><br><b>P01</b> = -30 inHg-0 psi<br><b>P03</b> = -30 inHg-0-30 psi<br><b>P16</b> = 0-30 psi<br><b>P18</b> = 0-100 psi<br><b>P20</b> = 0-200 psi<br><b>P21</b> = 0-300 psi<br><b>P25</b> = 0-1,000 psi<br><b>P34</b> = 0-5,000 psi<br><br><b>Available Ranges</b><br>■ Vac to 20,000 psi<br>■ Gauge Pressure, Vacuum, or Compound<br>■ Lowest Range = 10 psi<br><br><b>Available Units:</b><br>■ psi (std) ■ bar<br>■ kPa ■ kg/cm <sup>2</sup><br>■ ft H <sub>2</sub> O ■ & more | <b>-D</b> = Dry<br><b>-G</b> = Glycerin<br><b>-S</b> = Silicone<br><b>-W</b> = Glycerin/Water (65/35)<br><b>-I</b> = Inert | <b>-T</b> = Tempered Safety Glass (std)<br><b>-P</b> = Plastic<br><b>-S</b> = Laminated Safety Glass | <b>-HV</b> = Hi-Vis™ Dial<br><b>-C3</b> = 3 pt. Calibration Certificate<br><b>-OX</b> = Cleaned for O <sub>2</sub> Service<br><b>-TS</b> = Stainless Steel Tag<br><b>-MP</b> = Max. Pointer<br><b>-EC</b> = Electrical Contacts (4" Case Only)<br><b>-P6</b> = Pointer Stop at 6 O'clock<br><b>-R2</b> = .5% Full Scale Accuracy<br><b>-NC</b> = NACE Compliance Certificate<br><b>-PM</b> = Positive Material Identification Certification |

For Additional Range Codes See Page 45

## Diaphragm Seal Suitability Guide

\*Non-standard Configuration

For applications where a diaphragm seal is required, the following diaphragm seal model types are most commonly assembled and filled to Series PR40/60 pressure gauges. This matrix identifies which diaphragm seal is appropriate based on the specified pressure range. Please reference the diaphragm seal data sheet and seal fill fluid guide for additional application considerations including max pressure, temperature limits, and material compatibility.

| Diaphragm Seal Model |          | Total Gauge Span* (in psi) |    |    |    |    |     |      |
|----------------------|----------|----------------------------|----|----|----|----|-----|------|
|                      |          | 15                         | 30 | 45 | 60 | 75 | 100 | 160+ |
| Mini Seals           | MS6      | X                          | S  | T  | T  | T  |     |      |
|                      | MS8      | T                          | T  | T  |    |    |     |      |
| Threaded Flush       | 1"       | X                          | X  | X  | S  | T  | T   |      |
|                      | 1.5"     | T                          | T  | T  | T  |    |     |      |
| Offline              | W5       | S                          | T  | T  |    |    |     |      |
|                      | W6       | T                          |    |    |    |    |     |      |
|                      | W7/T5/V5 |                            |    |    |    |    |     |      |
| Sanitary             | 1.5" TC  | X                          | X  | X  | T  | T  | T   |      |
|                      | 2" TC    | S                          | T  | T  |    |    |     |      |

\*Total gauge span is additive of negative and positive pressures.

Example: -15 - 0 - 30 psi = 45 psi span

Assembly will function correctly with minimal accuracy degradation.

Assembly will function correctly given stable temperature.

Assembly is highly sensitive to orientation and temperature variance. REOTEMP cannot guarantee a stated accuracy.

Assembly will not work. The diaphragm does not displace enough fill fluid to drive the pressure gauge.

## PRESSURE GAUGE RANGES AND CODES

### VACUUM/COMPOUND RANGES

| psi       |           | Dual Scale & psi & Metric |                |                          |                               |           |                    | Single Scale-Metric |          |                    |                         |      |              |
|-----------|-----------|---------------------------|----------------|--------------------------|-------------------------------|-----------|--------------------|---------------------|----------|--------------------|-------------------------|------|--------------|
| "Hg/0/psi |           | psi & bar                 |                | psi & kg/cm <sup>2</sup> |                               | psi & kPa |                    | bar                 |          | kg/cm <sup>2</sup> |                         | kPa  |              |
| Code      | Range     | Code                      | Range          | Code                     | Range                         | Code      | Range              | Code                | Range    | Code               | Range                   | Code | Range        |
| P01       | -30"Hg/0  | D01                       | "Hg & -1/0 bar | G01                      | "Hg & -1/0 kg/cm <sup>2</sup> | L01       | "Hg & -100/0 kPa   | B00                 | -1/0 bar | K00                | -1/0 kg/cm <sup>2</sup> | A00  | -100/0 kPa   |
| P02       | -30/0/15  | D02                       | psi & -1/0/1   | G02                      | psi & -1/0/1                  | L02       | psi & -100/0/100   | B01                 | -1/0/1   | K01                | -1/0/1                  | A01  | -100/0/100   |
| P03       | -30/0/30  | D03                       | psi & -1/0/2   | G03                      | psi & -1/0/2                  | L03       | psi & -100/0/200   | B02                 | -1/0/2   | K02                | -1/0/2                  | A02  | -100/0/200   |
| P04       | -30/0/60  | D04                       | psi & -1/0/4   | G04                      | psi & -1/0/4                  | L04       | psi & -100/0/400   | B04                 | -1/0/4   | K04                | -1/0/4                  | A04  | -100/0/400   |
| P05       | -30/0/100 | D05                       | psi & -1/0/7   | G05                      | psi & -1/0/7                  | L05       | psi & -100/0/700   | B07                 | -1/0/7   | K07                | -1/0/7                  | A07  | -100/0/700   |
| P06       | -30/0/160 | D06                       | psi & -1/0/11  | G06                      | psi & -1/0/11                 | L06       | psi & -100/0/1,100 | B011                | -1/0/11  | K011               | -1/0/11                 | A011 | -100/0/1,100 |
| P07       | -30/0/200 | D07                       | psi & -1/0/14  | G07                      | psi & -1/0/14                 | L07       | psi & -100/0/1,400 | B014                | -1/0/14  | K014               | -1/0/14                 | A014 | -100/0/1,400 |
| P08       | -30/0/300 | D08                       | psi & -1/0/20  | G08                      | psi & -1/0/20                 | L08       | psi & -100/0/2,000 | B020                | -1/0/20  | K020               | -1/0/20                 | A020 | -100/0/2,000 |

### PRESSURE RANGES

| psi  |          | Dual Scale & psi & Metric |               |                          |                             |           |                 | Single Scale-Metric |         |                    |                        |      |           |
|------|----------|---------------------------|---------------|--------------------------|-----------------------------|-----------|-----------------|---------------------|---------|--------------------|------------------------|------|-----------|
| psi  |          | psi & bar                 |               | psi & kg/cm <sup>2</sup> |                             | psi & kPa |                 | bar                 |         | kg/cm <sup>2</sup> |                        | kPa  |           |
| Code | Range    | Code                      | Range         | Code                     | Range                       | Code      | Range           | Code                | Range   | Code               | Range                  | Code | Range     |
| P14  | 0-10 psi | D14                       | psi & .7 bar  | G14                      | psi & .7 kg/cm <sup>2</sup> | L14       | psi & 70 kPa    |                     |         |                    |                        |      |           |
| P15  | 0-15     | D15                       | psi & 0-1     | G15                      | psi & 0-1                   | L15       | psi & 0-100     | B1                  | 0-1 bar | K1                 | 0-1 kg/cm <sup>2</sup> | A1   | 0-100 kPa |
| P16  | 0-30     | D16                       | psi & 0-2     | G16                      | psi & 0-2                   | L16       | psi & 0-200     | B2                  | 0-2     | K2                 | 0-2                    | A2   | 0-200     |
| P17  | 0-60     | D17                       | psi & 0-4     | G17                      | psi & 0-4                   | L17       | psi & 0-400     | B4                  | 0-4     | K4                 | 0-4                    | A4   | 0-400     |
| P18  | 0-100    | D18                       | psi & 0-7     | G18                      | psi & 0-7                   | L18       | psi & 0-700     | B7                  | 0-7     | K7                 | 0-7                    | A7   | 0-700     |
| P19  | 0-160    | D19                       | psi & 0-11    | G19                      | psi & 0-11                  | L19       | psi & 0-1,100   | B11                 | 0-11    | K11                | 0-11                   | A11  | 0-1,100   |
| P20  | 0-200    | D20                       | psi & 0-14    | G20                      | psi & 0-14                  | L20       | psi & 0-1,400   | B14                 | 0-14    | K14                | 0-14                   | A14  | 0-1,400   |
| P21  | 0-300    | D21                       | psi & 0-20    | G21                      | psi & 0-20                  | L21       | psi & 0-2,000   | B20                 | 0-20    | K20                | 0-20                   | A20  | 0-2,000   |
| P22  | 0-400    | D22                       | psi & 0-28    | G22                      | psi & 0-28                  | L22       | psi & 0-2,800   | B28                 | 0-28    | K28                | 0-28                   | A28  | 0-2,800   |
| P23  | 0-600    | D23                       | psi & 0-40    | G23                      | psi & 0-40                  | L23       | psi & 0-4,000   | B40                 | 0-40    | K40                | 0-40                   | A40  | 0-4,000   |
| P24  | 0-800    | D24                       | psi & 0-55    | G24                      | psi & 0-55                  | L24       | psi & 0-5,500   | B55                 | 0-55    | K55                | 0-55                   | A55  | 0-5,500   |
| P25  | 0-1,000  | D25                       | psi & 0-70    | G25                      | psi & 0-70                  | L25       | psi & 0-7,000   | B70                 | 0-70    | K70                | 0-70                   | A70  | 0-7,000   |
| P30  | 0-1,500  | D30                       | psi & 0-100   | G30                      | psi & 0-100                 | L30       | psi & 0-10,000  | B100                | 0-100   | K100               | 0-100                  | A100 | 0-10,000  |
| P31  | 0-2,000  | D31                       | psi & 0-140   | G31                      | psi & 0-140                 | L31       | psi & 0-14,000  | B140                | 0-140   | K140               | 0-140                  | A140 | 0-14,000  |
| P32  | 0-3,000  | D32                       | psi & 0-200   | G32                      | psi & 0-200                 | L32       | psi & 0-20,000  | B200                | 0-200   | K200               | 0-200                  | A200 | 0-20,000  |
| P33  | 0-4,000  | D33                       | psi & 0-280   | G33                      | psi & 0-280                 | L33       | psi & 0-28,000  | B280                | 0-280   | K280               | 0-280                  | A280 | 0-28,000  |
| P34  | 0-5,000  | D34                       | psi & 0-350   | G34                      | psi & 0-350                 | L34       | psi & 0-35,000  | B350                | 0-350   | K350               | 0-350                  | A350 | 0-35,000  |
| P35  | 0-6,000  | D35                       | psi & 0-400   | G35                      | psi & 0-400                 | L35       | psi & 0-40,000  | B400                | 0-400   | K400               | 0-400                  | A400 | 0-40,000  |
| P36  | 0-8,000  | D36                       | psi & 0-550   | G36                      | psi & 0-550                 | L36       | psi & 0-55,000  | B550                | 0-550   | K550               | 0-550                  | A550 | 0-55,000  |
| P37  | 0-10,000 | D37                       | psi & 0-700   | G37                      | psi & 0-700                 | L37       | psi & 0-70,000  | B700                | 0-700   | K700               | 0-700                  | A700 | 0-70,000  |
| P38  | 0-15,000 | D38                       | psi & 0-1,000 | G38                      | psi & 0-1,000               | L38       | psi & 0-100,000 | B1K                 | 0-1,000 | K1K                | 0-1,000                | A1K  | 0-100,000 |
| P39  | 0-20,000 | D39                       | psi & 0-1,400 | G39                      | psi & 0-1,400               | L39       | psi & 0-140,000 |                     |         |                    |                        |      |           |
| P40  | 0-30,000 | D40                       | psi & 0-2,000 | G40                      | psi & 0-2,000               | L40       | psi & 0-200,000 |                     |         |                    |                        |      |           |
| P41  | 0-40,000 | D41                       | psi & 0-2,800 | G41                      | psi & 0-2,800               | L41       | psi & 0-280,000 |                     |         |                    |                        |      |           |
| P42  | 0-50,000 | D42                       | psi & 0-3,500 | G42                      | psi & 0-3,500               | L42       | psi & 0-350,000 |                     |         |                    |                        |      |           |



**Don't See The Range You Need?** REOTEMP has thousands of specialty dial ranges available and will work with you to create a custom range, just contact REOTEMP customer service.

## PRESSURE GAUGE OPTIONS

|                       |                                                        | Heavy-Duty Industrial Gauges |      |      |      | Process Gauges |       |      | Stainless Steel Case Industrial Gauges |       |       | Commercial Gauges |         | Low Pressure Capsule Gauges |       |            | Test Gauges |
|-----------------------|--------------------------------------------------------|------------------------------|------|------|------|----------------|-------|------|----------------------------------------|-------|-------|-------------------|---------|-----------------------------|-------|------------|-------------|
| Part #                | Description                                            | PR25                         | PR35 | PR40 | PR60 | PT45P          | PT45T | PI45 | PM                                     | PG**C | PG**S | PD15/20/25        | PD35/40 | PC25N                       | PC25S | PC40/45/60 | PL60/45     |
| CASE FILL OPTIONS     |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -G                    | Glycerin Filled Case                                   | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | N/A  | ✓                                      | ✓     | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -W                    | Glycerin Water Filled Case (65/35)                     | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | N/A  | ✓                                      | ✓     | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -S                    | Silicone Filled Case                                   | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | N/A  | ✓                                      | N/A   | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -T                    | Teflon-coated Movement (No case fill)                  | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | ✓     | ✓          | ✓           |
| -I                    | Inert Case Fill                                        | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | N/A  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| LENS OPTIONS          |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -P                    | Plastic Lens                                           | STD                          | ✓    | ✓    | ✓    | ✓              | ✓     | STD  | STD                                    | STD   | ✓     | ✓                 | MQ      | ✓                           | ✓     | ✓          | ✓           |
| -T                    | Tempered Safety Glass Lens                             | ✓                            | STD  | STD  | STD  | STD            | STD   | N/A  | N/A                                    | N/A   | STD   | N/A               | N/A     | N/A                         | STD   | STD        | STD         |
| -S                    | Laminated Safety Glass Lens                            | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | N/A  | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | ✓     | ✓          | ✓           |
| -G                    | Plain Glass                                            | N/A                          | N/A  | N/A  | N/A  | N/A            | N/A   | N/A  | MQ                                     | MQ    | N/A   | MQ                | STD     | N/A                         | N/A   | N/A        | N/A         |
| POINTER OPTIONS       |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -RP                   | Red Pointer                                            | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | ✓     | ✓          | ✓           |
| -MP                   | Min/Max Pointer (Drag Hand)†                           | ✓                            | N/A  | ✓    | ✓    | ✓              | N/A   | N/A  | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -MQ                   | Min/Max Pointer (Tamper-proof)†                        | ✓                            | N/A  | ✓    | ✓    | ✓              | N/A   | N/A  | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -RH                   | Red Set Hand (Manual Adjustment)                       | N/A                          | N/A  | N/A  | N/A  | ✓              | N/A   | N/A  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -EC                   | Electrical Contacts                                    | N/A                          | N/A  | ✓    | N/A  | ✓              | N/A   | N/A  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| DIAL OPTIONS          |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -CL                   | Custom Logo Dial                                       | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | MQ                                     | MQ    | ✓     | MQ                | MQ      | MQ                          | ✓     | ✓          | ✓           |
| -HV                   | Hi-Vis Dial                                            | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | ✓     | ✓          | N/A         |
| -CB                   | Color Band                                             | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | MQ                                     | MQ    | ✓     | MQ                | MQ      | MQ                          | ✓     | ✓          | N/A         |
| -CP                   | Color Pie                                              | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | MQ                                     | MQ    | ✓     | MQ                | MQ      | MQ                          | ✓     | ✓          | N/A         |
| -DM                   | Dial Marking                                           | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | MQ                                     | MQ    | ✓     | MQ                | MQ      | ✓                           | ✓     | ✓          | ✓           |
| -LP                   | Removable Lens Protector                               | N/A                          | N/A  | N/A  | N/A  | ✓              | ✓     | ✓    | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| CALIBRATION OPTIONS   |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -R1                   | Upgrade to 1% FS Accuracy                              | ✓                            | ✓    | STD  | STD  | N/A            | N/A   | N/A  | N/A                                    | N/A   | ✓     | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -R2                   | Upgrade to 0.5% FS Accuracy                            | N/A                          | N/A  | ✓    | ✓    | STD            | STD   | STD  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |
| -R5                   | Upgrade to 1.5% FS Accuracy                            | ✓                            | ✓    | N/A  | N/A  | N/A            | N/A   | N/A  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | ✓     | ✓          | N/A         |
| -C1                   | 1pt. NIST Calibration Cert                             | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | N/A         |
| -C3                   | 3pt. NIST Calibration Cert                             | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | N/A         |
| -C5                   | 5pt. NIST Calibration Cert                             | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | N/A         |
| -CX                   | 10pt. NIST Calibration Cert                            | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | STD         |
| -CS                   | Calibration Sticker (No logged pts.)                   | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | N/A         |
| TAG OPTION            |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -TS                   | Stainless Steel Tag (1-10 Characters)                  | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| -TM                   | Stainless Steel Tag (11-80 characters)                 | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| -TP                   | Paper Tag                                              | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| CERTIFICATION OPTIONS |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -CM                   | General Material Conformance                           | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| -NC                   | Certificate of NACE Compliance                         | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | ✓     | ✓          | ✓           |
| -PM                   | Positive Material Identification Certificate (PMI)     | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| -HT                   | Hydrostatic Test per ASME B31.3 (5 min)                | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| -LC                   | Argon Leak Check Certificate                           | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | ✓                                      | ✓     | ✓     | ✓                 | ✓       | ✓                           | ✓     | ✓          | ✓           |
| CLEANING OPTIONS      |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -DG                   | Degreased - Wiped Clean of Oils, Shipped in Sealed Bag | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | ✓     | N/A               | N/A     | ✓                           | ✓     | ✓          | ✓           |
| -OX                   | Cleaned for Oxygen Service per ASME B40.1              | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | MQ                                     | MQ    | ✓     | MQ                | MQ      | ✓                           | ✓     | ✓          | ✓           |
| -OY                   | Cleaned for Oxygen Service per MIL-STD-1330D           | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | ✓     | N/A               | N/A     | ✓                           | ✓     | ✓          | ✓           |
| OTHER OPTIONS         |                                                        |                              |      |      |      |                |       |      |                                        |       |       |                   |         |                             |       |            |             |
| -NR                   | No Restrictor Screw                                    | ✓                            | ✓    | ✓    | ✓    | ✓              | ✓     | ✓    | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | ✓          | N/A         |
| -FI                   | Dry Gauge Shipped with Fill Plug Installed             | N/A                          | N/A  | N/A  | N/A  | ✓              | N/A   | N/A  | N/A                                    | N/A   | N/A   | N/A               | N/A     | N/A                         | N/A   | N/A        | N/A         |

✓ Indicates that the option is available with the model.

STD Indicates standard options with no additional cost.

N/A Indicates the option is not available with this model.

MQ Minimum order quantity applies.

†This option is only available with a plastic lens.