

4" (101mm) Pressure Chart Recorder



Specifications

Ambient Operating RH Conditions : 0-95% RH non-condensing

Ambient Operating Temperature Conditions: -22 to 122F (-30 to 50C)

Battery Life (Avg): 1 Year

Calibration Options: N100, N300

Channels: CH1: Pressure

Chart Rotation Speed: 7 Day or 24 Hour Switchable

Dimensions: 6.25 x 6 x 2.9in

Enclosure: Velox PBT NEMA 4X with Polycarbonate Door Window (Weather/Water Resistant)

Fitting: 1/4" NPT Thread, 5/8" Hex

IP Rating: 66

Included Accessories: One AA Battery, Red Pen and Quick Start Guide. *Charts sold separately.

Mounting Options: Stem or Wall Mount (With Keyhole)

Power Source: Battery; One AA Battery (User Replaceable)

Pressure Accuracy: 2% of Full Scale

Pressure Range: 0 to 100PSI

Response Time: 1 Second

Unit Weight: 1.8 lbs

Units/Pkg: 1


Warranty: 12-Month Limited

Calibrations

N100: 1-Point NIST Traceable Calibration

N300: 3-Point NIST Traceable Calibration

Accessories



A791 - Pressure Kit

Pressure Fitting Accessory Kit



R022 - Pressure Filter Kit

Filter Kit includes Snubber



R006 - AA Battery

AA Alkaline Battery



A793 - Hydrant Kit

Fire Hydrant Adapter Kit

Accessories



A792 - Pressure Pigtail
Steam Pressure Pigtail