

**Delmhorst®** **75**  
- YEARS -  
1946 - 2021  
**INSTRUMENT CO**  
WHEN ACCURACY IS THE POINT.®

MOISTURE METERS

Introducing the new  
**PX-20 & PX-30**

Moisture Meters for Paper, Cores, and Baled Paper Products



The next generation of moisture meters is here, with the introduction of the **Navigator™** series and **EDGE™** app from Delmhorst.

## Delmhorst introduces the new **PX-20 & PX-30 MOISTURE METERS**

The **PX-20 and PX-30** are the latest in the new Navigator™ family of moisture meters from Delmhorst. Uniquely designed for use in the field, the PX-20 and PX-30 feature a dashboard-like display that is easy to read under most conditions, and large, easy to use navigation buttons.

With the **PX-20 and PX-30 Digital Paper Meters**, the contact pins mounted on the top of the meter are used for making direct contact with the material. Various external electrodes are also available for specific applications. The PX-20 and PX-30 are especially useful for testing paperboard, corrugated stock, and paper cores and tubes. They are ideal for QC personnel, buyers, and salespeople.

The **PX-30** includes Bluetooth®, enabling connection to the Delmhorst **EDGE™ app** with customizable settings and the ability to share the data from anywhere.



### Features

- Large, custom display with auto backlight – easy to read under all conditions
- On-screen readings statistics – High, Low, Average, Standard Deviation, view all readings
- Moisture Range:
  - 4.3%-18% MC for paper (kraft paper calibration)
  - 5%-40% for baled scrap paper
  - 0 - 100 reference scale for obtaining relative moisture levels on other materials without calibration
- Bluetooth® connectivity (PX-30)
- Color-coded LEDs – adjustable through **EDGE™** app (PX-30)
- Alarm set point - alerts to user-selected MC level
- Internal calibration check
- "Low Batt" warning with audio
- Auto off timer - set to 1m, 4m, or 10m
- Compatible with existing Delmhorst prods and electrodes (*see below*)

### The Delmhorst **EDGE™** app offers:

- Timestamp and geotag
- Data export to .csv format
- Save unlimited readings
- Customized LED ranges

### Meter Specifications:

- Power: 2x AA batteries
- QR code on meter for easy access to support materials and meter registration
- Size: meter only - 8.65in x 2.85in x 1.55in (2.2mm x 72mm x 39mm)
- Weight: meter only - 0.4.5oz (1.3g)
- Hard plastic carrying case included
- 2-year limited warranty on manufacturer's defects; bonus 3-month extended warranty with on-line registration