

Part No.

# QTFT-3MS0-RS-D6

*G3/8 with internal sealing x Male Quick-test with cap and chain, stainless steel*

Connect Female BSPP (ISO 228/1) parallel thread to Quick-test hose for temporary installation



QTFT-3MS0-RS-D6

## Specs/Attributes

|                           |                                                                                                                                                                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatible with           | Druck DPI 611, Druck DPI 612, Druck PV621, Druck PV621G, Druck PV621-IS, Druck PV622, Druck PV622G, Druck PV622-IS, Druck PV623, Druck PV623G, Druck PV623-IS, Druck MC620, Druck MC620G, Druck MC620-IS, Druck DPI705E, Druck DPI705E-IS, Druck PM700E, Druck PM700E-IS |
| Country of origin         | USA                                                                                                                                                                                                                                                                      |
| Materials                 | Stainless Steel                                                                                                                                                                                                                                                          |
| Max Operating Temperature | 225 °F / 105 °C                                                                                                                                                                                                                                                          |
| Max Pressure              | 5000 PSI / 350 bar / 35 MPa                                                                                                                                                                                                                                              |
| Min Operating Temperature | 0 °F / -18 °C                                                                                                                                                                                                                                                            |
| Seal Materials            | Buna-N                                                                                                                                                                                                                                                                   |
| Connector End 1           | G 3/8 Male BSPP (ISO 228)                                                                                                                                                                                                                                                |
| Connector End 2           | Male Quick-test                                                                                                                                                                                                                                                          |
| Dimensions                | H: 1.28 in (3.25 cm) x W: 0.88 in (2.24 cm)                                                                                                                                                                                                                              |