Part No.

QTHA-KIT34-SS

BSPP to Quick-test low pressure hand pump conversion kit, stainless steel

Convert hand pumps or other devices with BSPP connections to Ralston Quick-test



QTHA-KIT34-SS

Included Items

- Adapter G 1/8" male BSPP (ISO 228/1) x male Quick-test, no check-valve, stainless steel (QTHA-1MSO-RS)
- Bonded Seal 1/8" male RS bonded seal ring, steel and Buna-N (QTHA-1BR-RS)
- Adapter G 1/8" male BSPP (ISO 228/1) x male Quick-test, no check-valve, with cap and chain, stainless steel (QTFT-1MSO-RS)
- Bonded Seal 1/8" male RS bonded seal ring, steel and Buna-N (QTHA-1BR-RS)
- Hose Quick-test 6900 psi hose, S.S. hose ends, 1 m (3.3 ft) long (QSQS-HOS-1m)
- Adapter 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)

Specs/Attributes

Compatible with	Fluke 700LTP-1

Adapter QTHA-2MS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Bonded Seal OTHA-1BR-RS



Bonded Seal QTHA-1BR-RS

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Plated Steel
Seal Materials	Buna-N
Country of origin	USA

Hose QSQS-HOS-1m

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air,Inert Gas,Natural Gas,Petroleum Based Oil,Water
Hose Length	1 m / 3.28 ft
Inner Diameter	0.08 In / 3.00 mm
Length	1.00 m / 3 ft 3 in
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 ln / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Туре	QT