

Part No.

QTHA-KIT36-SS

NPT to Quick-test medium pressure hand pump conversion kit, SS adapters

Convert to medium pressure hand pumps with NPT connections to the Ralston Quick-test system



QTHA-KIT36-SS

Included Items

- Adapter - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- Adapter - 1/4" male NPT x male Quick-test, no check-valve, S.S. (QTHA-2MS0)
- Adapter - 1/8" male NPT x male Quick-test, no check-valve, with cap and chain, S.S. (QTFT-1MS0)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)

Adapter QTFT-1MS0

Country of origin	USA
Has Cap and Chain	Yes
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	Male Quick-test
Connector End 2	1/8" Male NPT (ASME B1.20.1)
Dimensions	H: 1.76 in (4.47 cm) x W: 0.71 in (1.8 cm)

Hose QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm

Hose QSQS-HOS-3ft

Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT