Part No.

THA-KIT38-SS

Premium Transmitter Test Hose Kit, Stainless steel adapters

Kit containing (2) 1/8" MNPT, (2) 1/4" MNPT, (1) 1/4" MNPT Quick-connect, (1) 1/4" BSPP Quick-test adapters, S.S., (1) 3ft Quick-test hose, 2 replacement o-rings, nylon bag



QTHA-KIT38-SS

Included Items

- Process Connection 1/8" male NPT x male Quick-test, no check-valve, with cap and chain, S.S. (QTFT-1MS0)
- Process Connection 1/8" male NPT x male Quick-test, no check-valve, with cap and chain, S.S. (QTFT-1MS0)
- Process Connection 1/4" male NPT x male Quick-test, no check-valve, with cap and chain, S.S. (QTFT-2MS0)
- Process Connection 1/4" male NPT x male Quick-test, no check-valve, with cap and chain, S.S. (QTFT-2MS0)
- Process Connection G 1/4" male BSPP (ISO 228/1) x male Quick-test, no check-valve, S.S. (QTHA-2MS0-RS)
- Process Connection 1/4" male NPT QD (Quick-connect) Adapter, S.S. (QTHA-2MS0-QD)
- Bonded Seal 1/4" male RS bonded seal ring, steel and Buna-N (QTHA-2BR-RS)
- O-ring Replacement o-ring for QTHA-2MSO-QD (SO-2111-BN)
- O-ring Replacement o-ring for QTHA-2MSO-QD (SO-2111-BN)
- Hose Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Thread Sealant PTFE sealing tape, 0.5 inches wide, 10,000 psi, UL Listed (SM-0090)
- Bag Zippered bag to hold hose and adapters, nylon (SM-0084)

Process Connection OTHA-2MSO-OD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.88 in (4.78 cm) x W: 1 in (2.54 cm)

Bonded Seal OTHA-2BR-RS

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa

Bonded Seal QTHA-2BR-RS

Materials	Plated Steel
Seal Materials	Buna-N
Country of origin	USA

O-ring SO-2111-BN

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Country of origin	USA

Hose QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 ln / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Туре	QT

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6 in (15.24 cm) x W: 1 in (2.54 cm) x D: 7 in (17.78 cm)