



### Features

- Built-in laser pointer identifies target area
- User selectable °F or °C
- 50:1 Distance to Spot size ratio
- Bright color display (EBTN)
- Digitally adjustable emissivity
- Max, Min, Average and Differential readings
- Audible (beep) and visual (tri-color LED) user adjustable alarms
- Internal memory stores up to 5 pre-set high & low alarms and 5 emissivity settings
- Trigger lock and tripod mount for continuous monitoring
- Low battery indication and auto shut off
- Includes carrying case and battery

Tri-color LEDs quickly indicate when temperatures are within (green), above (red) or below (blue) set parameters.



### Specifications

Temperature Range:

Accuracy:

Resolution:

Optical Resolution (D:S):

Laser Optimization Distance:

Repeatability:

Dual Laser:

Spectral Response:

Emissivity:

Response Time:

Backlit Display:

Display Hold:

High/Low Alarms:

Alarm Indicators:

Max/Min:

Average and Differential:

F/C Switchable:

Trigger Lock:

Internal Memory:

Tripod Mountable:

Laser Class:

Low Battery Indicator:

Power Supply:

Battery Life:

Product Certifications:

Operating Temperature:

Storage Temperature:

Operating Humidity Range:

Maximum Operating Altitude:

Maximum Storage Altitude:

Dimensions:

Weight:

### TECHNICAL DATA

-26 to 2282°F (-32 to 1250°C)

Basic:

±1.8% of reading or 3.6°F (1.8°C),

"or": choose whichever is greater

Detailed:

≥0°C: ±1.8°C or ±1.8% of reading,

"or": choose whichever is greater

Detailed:

<0°C: ±[1.8°C+0.1°C/°C]

≥32°F: ±3.6°F or ±1.8% of reading,

"or": choose whichever is greater

<32°F: ±[3.6°F+0.1°F/°F]

0.1°F (0.1°C)

50:1

5.2' (1.6m)

0.8°C or 0.8%,

whichever is greater

(1.8°F or 0.8%, whichever is greater)

Yes

8 to 14μm

0.1 to 1.0 (Adjustable)

250ms

Yes (Color EBTN)

Yes

Yes (audible and visual)

LED (High: Red, Low: Blue)

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Class II

Yes

9V Battery

Approx. 10 hours

(with continuous use,

backlight on)

CE, RoHS

32 to 122°F (0 to 50°C)

-4 to 140°F (-20 to 60°C)

10 to 90%

6561' (2000m)

39370' (12000m)

7 x 4.98 x 2"

(179 x 126.5 x 53mm)

10.95oz (310g)

Model	Description
R2330	Infrared Thermometer
R2330-NIST	Infrared Thermometer with NIST