

RHDL50 USB Temperature/Humidity Datalogger with display

with built-in 2000 count LCD display

Features:

- Record up to 16,000 readings each for Temperature and Humidity
- User adjustable sampling rate from 2 seconds to 24 hours
- High/Low Alarms with visual alert when settings are exceeded
- 2 LEDs indicate status
- USB interface for transferring recorded data to your PC
- Optional model complete with Certificate of Traceability to N.I.S.T.
- Includes 3.6V Lithium battery and analysis software



Applications:

Record Temperature and Humidity for long periods of time in virtually any indoor setting

Eliminate manual recording of data, monitor labs, greenhouses, warehouses, HVAC systems, storage areas, office space, classrooms, museums and more

Specifications

Temperature	-40 to 158°F (-40 to 70°C)
Accuracy	±1.8°F/1.0°C
Relative Humidity	0 to 100%RH
Accuracy	±3.5%RH
Resolution	0.1°F/°C; 0.1%RH
Datalogging Points	16,000 Temperature / 16,000 Humidity
Sampling Intervals	2sec to 24hr
PC Interface	USB
Power	3.6V Lithium Battery
Dimensions	5.1 x 1.2 x 1" (130 x 30 x 25mm)
Weight	0.7oz (20g)

Ordering Information:

RHDL50 USB Temperature/Humidity Datalogger with display
RHDL50-NIST RHDL50 Including Certificate of Traceability to N.I.S.T.