



Empowering you to work smarter

SK2SV1

Smart Refrigerant Flow Control Kit



Compatible with *myNAVAC™* App



**A2L
Compatible**



Automatic Refrigerant Charging & Recovery

NRS2A Smart Refrigerant Scale

- Precise measurement at 0.05% accuracy
- Magnesium alloy weighing platform
- Handheld device included
- Impact resistant design

Model	NRS2A
Maximum load	220 lbs (100 kg)
Accuracy	0.05%FS
Resolution	0.2 oz
Battery Type	4 × AA (Scale), 4 × AAA (Handheld)
Battery Operating Time	150 Hrs (Scale), 65 Hrs (Handheld backlight off)
Weight	3.3 lbs
Accessory	Carry bag

1-YEAR WARRANTY

NSV1 Smart Refrigerant Valve

- Status indicator for Flow, Bluetooth Connection, and Power
- Fast, low-latency operation
- Rechargeable lithium battery
- Impact resistant design, IP54 rating

Model	NSV1
Maximum Working Pressure	551 psi
Ports	1/12" (2 mm)
Operating Environment	14~122°F (-10~50°C)
Storage Temperature	14~122°F (-10~50°C)
Power Supply	Rechargeable 1000mAh Lithium Battery
Rechargeable Battery Operating Time	60 hours
Bluetooth Range	>100'
Dimensions	4.76"H × 3.62"W × 1.87"D
Unit Weight	1.33 lbs
Accessory	Carry bag

