



Empowering you to work smarter



Compatible with *myNAVAC™* App

SK2TP1 SK3TPH1 Smart Probe Kit



SK2TP1
Smart Refrigerant Diagnostics Kit



SK3TPH1
Smart Refrigerant & Air Side Diagnostics Kit

Smart Charging & Comfort Diagnostics

Smart Probes with Digital Display

- Probes are suitable for standalone use
- Works wirelessly with myNAVAC™ App
- High accuracy sensors
- Built-in digital screen

NSP1 Bluetooth Pressure Probes

- Auto VSAT / LSAT calculations thru App
- Rechargeable lithium battery
- Easy-to-Switch Knob, suitable for either High (HP) or Low (LP) Side

NST1 NST2 Bluetooth Temperature Clamps

- 1-5/8" opening
- High accuracy thermistor sensor
- Bluetooth connection with NEXUS Digital Manifold Gauge

NSH1 Bluetooth Psychrometers

- Detailed psychrometric datapoints
- Rechargeable lithium battery
- Easy-to-switch knob, suitable for either Side Supply (SP) or Return (RT)

Model	NST1 (Low Side)	NST2 (High Side)	NSP1	NSH1
Description	Bluetooth Temperature Clamp	Bluetooth Temperature Clamp	Bluetooth Pressure Probe	Bluetooth Psychrometer
Measuring Range	-40~257°F (-40~125°C)	-40~257°F (-40~125°C)	-29~725 psi (-1~50 bar)	Humidity: 0~100% RH / Temp: -40~249.8°F
Accuracy	± 2.3°F (± 1.3°C)	± 2.3°F (± 1.3°C)	± 0.5%	Humidity: ±2.0%RH (10 to 90%RH) (at 77°F) ±5.0%RH (<10%RH or >90%RH) (at 77°F) Temperature: ±1.1°F (-4°F~32°F) ±0.9°F (32°F~140°F) ±1.3°F (140°F~248°F)
Resolution	0.1°F	0.1°F	0.01 psi	0.1%RH, 0.1°F
Battery Type	2 x AAA	2 x AAA	Rechargeable Lithium Battery	Rechargeable Lithium Battery
Unit Weight	5.6 oz	5.6 oz	7.8 oz	7.8 oz

1 YEAR WARRANTY

1.888.610.7664



www.calcert.com

sales@calcert.com