LevelPro® — ShoPro® Series Level Display | Controller





LevelPro® — ShoPro® Series Level Display | Controller





Features

- All-in-one | Out of the Box Ready to Use
- Visual Alarm High | Low Level
- 4-20mA Output + Relay Output
- Power Supply Output 24V DC
- **New Easy-Learn® Programming**
- NEMA 4X Enclosure
- **Corrosion Resistant Thermoplastic**
- Cord Grips Included No Tools Required

All-in-One Display & Controller

The ShoPro® Series Level Display | Controller is the industry's most rugged and reliable wall-mount remote display.

The ShoPro® comes as a complete all-in-one unit, out of the box it is ready to use. Included is a bright LED display, NEMA 4X enclosure, Polycarbonate faceplate, cord grips and plastic captive screws.

The industrial design ensures that it will withstand the industry's most corrosive environments. Available with two 5A relays + 4-20mA output.

Working Principle



Fill Pipe Clamp — No Drilling





Shown with optional audible and visual alarms





LevelPro® — ShoPro® Series

Level Display | Controller



Technical Specifications

General		
Display	LED 5 x 13mm High Red	
Displayed Values	9999 ~ 19999	
Transmission Parameters	n Parameters 1200115200 bit/s, 8N1 / 8N2	
Stability	50 ppm °C	
Housing Material	Material Polycarbonate	
Protection Class	tion Class NEMA 4X IP67	
Input Signal Supply		
Standard	Current: 4-20mA	
Voltage	85 - 260V AC/DC 16 - 35V AC, 19 - 50V DC*	
Output Signal Supply		
Standard	2 x Relays (5A) + 4-20mA	
Voltage	24VDC	
Passive Current Output *	Current Output * 4-20mA (Operating Range Max. 2.8 - 24mA)	
Performance		
Accuracy	0.1% @ 25°C One Digit	
Accuracy According to IEC 6077	0 - Limit Point Adjustment Non-Linearity Hysteresis Repeatability	
Temperatures		
Operating Temperatures	-20 to 158°F -29 to 70°C	
*0 .: 1		

^{*}Optional

Model Selection

ShoPi	ro® SP100 –	00 — Liquid Level LED Display
Part Number	Input	ut Output
SP100	4-20mA	mA 4-20mA
SP100-A	4-20mA	mA 2 Relay + 4-20mA + Audible
SP100-V	4-20mA	mA 2 Relay + 4-20mA + Visual
SP100-A-V	4-20mA	mA 2 Relay + 4-20mA + Audible & Visual

Shown with optional audible and visual alarms.

