

# WTSF 120

Product no.: T0051390799



## Benefits

- > Efficient, single-handed soldering
- > Nonstick coating inside solder feed tube (no flux adhesion; save on maintenance costs)
- > Integrated start / stop / standby functions conserves energy and extends the service life of the unit
- > Compatible with Weller WT1H, WT2M, WD 1M, WR 2, WR 3M rework station (sold separately)
- > Timer mode: a defined amount of solder is applied time the finger switch is pressed (LED on)
- > Pulse mode: the solder wire is continuously delivered as long as the switch is pressed (LED off)
- > Compatible with Weller WD1M, WR2, WR3M and WT soldering and rework base stations (sold separately)
- > Compatible with 0.5mm, 0.8mm, and 1.0 mm solder wire diameters
- > Consists of WTSF120 solder feeder unit, XTB (2.4 mm) soldering tip, 120W soldering iron with integrated solder feeder

Technical Data

Active Tip heating element technology	---
Power Response heating element technology	on
Silver Line heating element technology	---
Voltage	24 V AC
Power	120 W (126 W)
Tip range	XT
Supply unit	WD 1M, WSD 121, WR 2, WR 3M
WX-compatible	---
Temperature range °C	100 - 450
Temperature range °F	200 - 850
Heating time	14
Safety rest	---
Safety rest (optional)	---
Barrel	T0058763731
Integrated direct extraction	---