


Battery Quality Analyzer



Battery change time estimate

TEKON® 950

To prevent faults or quality issues in critical battery back-up applications caused by defects in stationary batteries, TEKON950 battery quality analyzer enables the user to diagnose and evaluate the performance and the degree of ageing by testing the conditions of individual batteries (500V max) in type of cell, module or pack. TEKON950 can handle virtually all battery testing (e.g. aged status of battery under test and the condition of a power system) in systems that use high-voltage battery packs, such as ESS, EV, HEV and PV as well as UPS.

Features

- Measures internal resistance of 500V max of batteries
- Measures voltages at battery (DC1000V)
- Measures voltage of UPS (AC500V)
- Measures ripple voltage, current and temperature
- Measures capacity of battery (Capacity)
- Diagnoses ageing of battery and predicts its use life (to determine timing for replacement)
- Can conduct history management of battery using 8MB memory
- Auto Hold and Data Storage
- Prints out measurement data in reports
- Transmits measurement data to remote locations (e-mail, server) using Mobile App
- Battery management using identification code

General specifications

Power [battery]	7.2V/5.2Ah Li-ion, 12V/2.5A DC adaptor
Data storage	8MB
Communication	Bluetooth Ver2.1 + EDR Class2
LCD display	4.0 monographic
Operating temp/ humidity	0°C ~ 45°C, RH 85% max
Storage temp/ humidity	-20°C ~ 60°C, RH 85% max
Compliant standards	IEC 61010-1 CAT III 500V Pollution Degree 2, EN61326-1:2013
Dimension	240(L)×198(W)×109(H) mm
Weight	1.4kg
Case Color	Black, Yellow, Orange

Electrical specifications

Measurement of resistance (Auto/Manual)

Range	Resolution	Measurable current	Accuracy
3mΩ	1uΩ	100mA	±0.8%rdg±10dgt
30mΩ	10uΩ	100mA	
300mΩ	100uΩ	10mA	
3Ω	1mΩ	1mA	
30Ω	10mΩ	0.1mA	
300Ω	100mΩ	0.1mA	±0.5%rdg±10dgt

DCV (Auto/Manual)

Range	5, 50, 500V
Resolution	1mV
Accuracy	±0.5%rdg±5dgt

ACV

Range	0-500V
Resolution	100mV
Frequency	40Hz-100Hz
Accuracy	±0.75%rdg±10dgt

Ripple voltage

Range	0-5V
Resolution	1mV
Frequency	40Hz-10Hz
Accuracy	±5.0%rdg±10dgt

Measurement of temperature

Range	-10°C ~ 100°C
Resolution	0.1°C
Accuracy	±1°C+2dgt

DC

Range	4, 40, 400A
Resolution	1mA
Accuracy	±0.5%rdg±5dgt (+CT Tolerance)

AC

Range	4, 40, 400A
Resolution	1mA
Accuracy	±0.75%rdg±10dgt (+CT Tolerance)

Measurement of capacity (950B)

Measuring method	Rated capacity, charge/discharge test
Range	0 ~ 100%
Measurable capacity	0 ~ 1200Ah
Parameters displayed	Efficiency, capacity, Ah, Average current, Charge-discharge time, Graph

Charge rate SOC (State of Charge) / 950B

Measuring method	Charge-discharge test
Range	0 ~ 100%
Measurable voltage	500V max
Cell under test	1.2V, 2V, 3.6V, 12V

Accessories

Standard	Pin-type Kelvin Probe, Test Lead, Li-ion battery (7.2V/5.2Ah), 12V/2.5A adaptor, Zero-Bar, Portable bag, PC Program, User's Manual, clamp-on/950B
Optional	Extensible rod (500mm), clamp, Clip-type Kelvin probe



40/400A Clamp



7.2V/5.2Ah
Li-ion battery Pack



Zero Bar



Extensible rod
(500mm)



Test Lead



Kevin Probe (Pin)



Kevin Probe (Clip)

Comparison of functions in TEKON950 Series

Function		TEKON950A	TEKON950B
Impedance	Scale	3mΩ-300Ω(6range)	3mΩ-300Ω(6range)
	Accuracy	±0.8%	±0.8%
	Max Test Voltage	200V	400V
DC/V		0-500V	0-500V
AC/V		0-500V	0-500V
Ripple Voltage		0-5V	0-5V
DC/A(Floating Current)		4A/40A/400A	4A/40A/400A
Ac/V(Ripple Current)		4A/40A/400A	4A/40A/400A
Temperature		NTC	NTC
Analyzer	Trend	○	○
	Change time	○	○
Capacity		×	○
Data record		8MB	8MB
PC Interface		Bluetooth	Bluetooth
External Interface		Mobile App	Mobile App
Auto Hold		○	○
Auto Record		○	○