



Personal Monitor For oxygen, toxic and flammable gases

Tetra

A personal monitor you can trust

Designed using the latest technologies, Tetra is simple to use, reliable, robust and fully weather protected.

Single button operation and intelligent sensor modules guarantee simplicity and flexibility of use.

The shockproof internal construction and self checking software assure reliable gas detection in the most arduous of environments.

Tetra, a personal monitor you can trust.

Reliable

- True single button operation – the most user friendly product available
- Li-ion rechargeable battery gives full 12 hours operation
- Easy to read backlit graphic display for gas readings and diagnostics
- Simple indications of operating status can be viewed at a glance
- 30 day countdown warning of calibration due date

Flexible

- Fully interchangeable intelligent sensor modules
- Available with internal electric sampling pump
- Rechargeable and alkaline battery versions available

Robust

- Tough plastic construction with flexible internal assembly to resist shock and vibration
- Overmoulded rubber for added protection
- Water and dust resistant to IP65

Assurance

- 94dBA audible alarm (@30cm)
- Piercingly bright dual red/blue visual alarm
- Internal vibrating alarm
- Two levels of instantaneous alarm
- Time weighted average alarm for 8 hours and 15 minute averages

Tetra

Specification

Weight	498g (1.1lb)			Operating temp. range	-20°C to +55°C (-4°F to +131°F)
Dimensions	122x128x57mm (4 ³ / ₄ x5x2 ¹ / ₂ inches) rechargeable 134x128x57mm (5 ¹ / ₄ x5x2 ¹ / ₂ inches) non-rechargeable			Humidity	0-99% RH
				Ingress Protection	IP65
Gas	Range	Alarm UK/ROW	Alarm US	Approval Codes	
Flammable	0-100%LEL	20%LEL	10%LEL	Europe:	ATEX II 2G EEx iad IIC T4 (Tamb -20°C to +55°C) BASEEFA 03ATEX0193
Oxygen	0-25%	19/23.5%	19.5/23.5%	USA	UL/cUL Class I Division 1 Groups A, B, C, D.
Hydrogen Sulphide	0-50ppm	5ppm	10ppm	Safety Standards	
Carbon Monoxide	0-500ppm	30ppm	35ppm	Europe	EN50014, EN50020, EN50018, 94/9/EC
Sulphur Dioxide	0-20ppm	2ppm	2ppm	USA & Canada	UL913, CSA22.2, 152
Chlorine	0-20ppm	0.5ppm	0.5ppm	Operation Standards	EN50270, EN50271, IEC61508, EN61779
Nitrogen Dioxide	0-10ppm	3ppm	3ppm	PC Interface	IR link for RS232 connection. USB/RS232 Converter available. Portables PC software package provides full configuration control, calibration and access to the Data and Event files.
Ammonia	0-100ppm	25ppm	25ppm	Autocalibrator	Tetra can be routinely calibrated using the Crowcon Autocalibrator II in conjunction with the Portables PC software.
Ozone	0-1ppm	0.1ppm	0.1ppm	Accessories	Tetra is supplied with an integral belt/pocket clip. Pumped units are supplied with a sampling kit (flowplate and 2m(6ft) tubing)
Hydrogen	0-1000ppm	N/A	N/A		
Hydrogen Cyanide	0-25ppm	5ppm	5ppm		
Hydrogen Chloride	0-10ppm	1ppm	1ppm		
Hydrogen Fluoride	0-10ppm	1ppm	1ppm		
Phosphine	0-5ppm	0.2ppm	0.2ppm		
Fluorine	0-1ppm	0.1ppm	0.1ppm		
Phosgene	0-1ppm	0.1ppm	0.1ppm		
Ethylene oxide	0-10ppm	1ppm	1ppm		
Nitric oxide	0-100ppm	25ppm	50ppm		
Other ranges and alarm levels are available on request. Each gas channel can have two instantaneous alarm levels set. Toxic channels also have Time Weighted Average alarms.					
Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.					
Typical response times	Flammable 20 s, Toxic gas 20 s, Oxygen 10s				
Audible Alarms	94dBA @ 30cm (1ft) Multiple alarm sounds allow selection of distinctive tones for different alarm levels				
Visible Alarms hazard	Dual colour red/blue flashing LED pair in gas				
Vibrating alarm	Internal vibrating alarm				
Display	128x64 graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), pump operation, healthy operation or fault warning. Start up indication when calibration is due within 30 days, calibration overdue, or service required.				
Display Mode	Normal display for real time gas concentration levels. Display recall for Peak readings and TWA				
Datalogging	Timed datalogging: 50 hours at 1-minute data rate Event logging: >1500 events				
Battery Types	Rechargeable Li-ion battery Non rechargeable pack 3xAA Alkaline cells				
Operating time	Based on pumped four gas unit with flammable sensor Rechargeable 12 hours minimum Non-rechargeable 11 hours minimum				
Sampling	Hand aspirator or internal electric sampling pump				

Gas Test Kit

The Gas Test Kit provides a simple and convenient means of carrying out either a pre-use (bump) test to verify that a Tetra is working within acceptable limits, or a simultaneous four gas calibration for flammable gas, oxygen, carbon monoxide and hydrogen sulphide.

The kit includes a 34 litre gas bottle containing a multigas mix with a special 'Trigger' regulator, a magnet and a clip-on flow plate configured either for diffusion or pumped units, all supplied in a convenient carry case. Separate kits are available for diffusion and pumped instruments.

Swiping the magnet past the Tetra display initiates a special test mode, then the gas is applied. The Tetra evaluates the response to the gas components against values stored in its memory and if it is within defined limits the Tetra signals a successful test. A test failure brings up an advisory calibration warning.

If the user performs a manually selected zero prior to test initiation Tetra offers



Gas Test Kit

The Gas Test Kit provides a simple and convenient means of carrying out either a pre-use (bump) test to verify that a Tetra is working within acceptable limits, or a simultaneous four gas calibration for flammable gas, oxygen, carbon monoxide and hydrogen sulphide.

The kit includes a 34 litre gas bottle containing a multigas mix with a special 'Trigger' regulator, a magnet and a clip-on flow plate configured either for diffusion or pumped units, all supplied in a convenient carry case. Separate kits are available for diffusion and pumped instruments.

Swiping the magnet past the Tetra display initiates a special test mode, then the gas is applied. The Tetra evaluates the response to the gas components against values stored in its memory and if it is within defined limits the Tetra signals a successful test. A test failure brings up an advisory calibration warning.

If the user performs a manually selected zero prior to test initiation Tetra offers the option of running a simultaneous four-gas calibration rather than just a verification test



A HALMA COMPANY

P01017 Issue 6 08/05

UK Office
Crowcon Detection Instruments Ltd
2 Blacklands Way
Abingdon Business Park

USA Office
Crowcon Detection Instruments Ltd
21 Kenton Lands Road
Erlanger

Rotterdam Office
Crowcon Detection Instruments Ltd
Vlambloem 129
3068JG, Rotterdam

Singapore Office
Crowcon Detection Instruments Ltd
Block 194 Pandan Loop
#06-20 Pantech Industrial Complex

1.888.610.7664



www.calcert.com

sales@calcert.com

Fax: +44 (0) 1235 557749
Email: crowcon@crowcon.com
Web Site: www.crowcon.com

Fax: +1 859 957 1044
Email: salesusa@crowcon.com
Web Site: www.crowcon.com

Web Site: www.crowcon.net

Web Site: www.crowcon.com

Crowcon reserves the right to change the design or specification of this product without notice