THERMALIMAGERS FOR ANDROID® & iOS DEVICES

Easily capture, store, and share thermal images and video





THERMAL IMAGERS FOR ANDROID® AND IOS DEVICES

The Klein Tools Thermal Imagers for Android and iOS have 10,800 pixels for excellent resolution to troubleshoot hot and cold spots. Features include touch-screen temperature; minimum, maximum, and differential temperature; user-selected high and low temperature alarms; and time-lapse video.

SPECIFICATIONS

Sensor Resolution 10,800 pixels Pixel Size 17 μm Spectral Response 8 to 14 μm Field of View 50° Frame Rate 9 Hz Focus Fixed Image/Video Formats JPG/MP4 Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs • Temp Bar • Differential Temp • Touchscreen Temp • Temp Scale °F or °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds • High/Low Temp Alarm • Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps Drop Protection 6.6 ft. (2m)				
Spectral Response 8 to 14 µm Field of View 50° Frame Rate 9 Hz Focus Fixed Image/Video Formats JPG/MP4 Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs Temp Bar • Differential Temp • Touchscreen Temp Temp Scale °F or °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds • High/Low Temp Alarm • Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Sensor Resolution	10,800 pixels		
Field of View 50° Frame Rate 9 Hz Focus Fixed Image/Video Formats JPG/MP4 Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale °F or °C Temp Range 'F or °C Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Pixel Size	17 μm		
Frame Rate 9 Hz Focus Fixed Image/Video Formats JPG/MP4 Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale °F or °C Temp Range °F or °C Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Spectral Response	8 to 14 μm		
Focus Fixed Image/Video Formats JPG/MP4 Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale °F or °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Field of View	50°		
Image/Video Formats Sensitivity Sensitivity High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale Fend Range -4 to 752°F (-20 to 400°C) Temp Resolution Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Frame Rate	9 Hz		
Sensitivity <60 mK at 25°C High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale For °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Focus	Fixed		
High, Low, and Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale Pror°C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Image/Video Formats	JPG/MP4		
Center Temp Crosshairs Temp Bar Differential Temp Touchscreen Temp Temp Scale For °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Sensitivity	<60 mK at 25°C		
Differential Temp Touchscreen Temp Temp Scale Temp Range Temp Range Temp Range Temp Range Temp Range Temp Resolution Temp Reso		•		
Touchscreen Temp Temp Scale F or °C Temp Range -4 to 752°F (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Temp Bar	•		
Temp Scale Temp Range C-20 to 400°C) Temp Resolution O.1°F, O.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity O.01 to 0.99 Time Lapse Intervals Yer For °C -4 to 752°F (-20 to 400°C) Temp Resolution O.1°F, 0.1°C Alarm Sounds Ironbow, Grayscale Emissivity O.01 to 0.99	Differential Temp	•		
Temp Range	Touchscreen Temp	•		
Temp Range (-20 to 400°C) Temp Resolution 0.1°F, 0.1°C Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Temp Scale	°F or °C		
Alarm Sounds High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Temp Range			
High/Low Temp Alarm Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Temp Resolution	0.1°F, 0.1°C		
Color Palettes Ironbow, Rainbow, Grayscale Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	Alarm Sounds	•		
Emissivity 0.01 to 0.99 Time Lapse Intervals 4, 8, or 16 fps	High/Low Temp Alarm	•		
Time Lapse Intervals 4, 8, or 16 fps	Color Palettes	Ironbow, Rainbow, Grayscale		
	Emissivity	0.01 to 0.99		
Drop Protection 6.6 ft. (2m)	Time Lapse Intervals	4, 8, or 16 fps		
	Drop Protection	6.6 ft. (2m)		

TI220 includes USB-C connector, micro-USB connector/adapter, and Hard Storage Case with Carabiner.





TI222 includes Hard Storage Case with Carabiner.

Fits phone cases up to 1/16" (1.5 mm). Phone cases thicker than 1/16" (1.5 mm) may require removal of case for secure connection.







For Professionals

SINCE 1857™







Easily capture, store, and share thermal images and video using the Klein Tools Thermal Imager App. Available for free on Google Play™ Store or App Store.

W CEUK 2m CEUK

Cat. No.	UPC 0-92644+	Description	Compatibility	Mobile App
TI220	69348-9	Thermal Imager for Android®	Android® 6.0 or higher	Google Play™Store
TI222	69361-8	Thermal Imager for iOS Devices	iOS 11 or higher with Lightning connectors	App Store

Android® a is a registered trademark of Google LLC. Google Play™ store is a trademark of Google LLC. App Store, iPhone, and Lightning are registered trademarks of Apple Inc., registered in the U.S. and other countries. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used by Apple, Inc. under license.