

### 3M™ Mat Product Selection Guide

| Construction                     | Primary Usage   | Features                                                                                                                                     | Color             | Model                                                                            | Rtt                    | Rtg                    | Roll (Runner) Widths                                       |
|----------------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------------------------------|------------------------|------------------------|------------------------------------------------------------|
| <b>Premium</b>                   |                 |                                                                                                                                              |                   |                                                                                  |                        |                        |                                                            |
| <b>2-Layer Rubber</b>            | Table           | Resistant to heat and most common solvents, excellent electrical properties, superior lay flat characteristics, thickness 0.065 in. (1.7 mm) | Gray, Blue, Green | 8800 Series                                                                      | 1 x 10 <sup>6</sup>    | 5 x 10 <sup>6</sup>    | 2 ft., 2.5 ft., 3 ft., 4 ft. (0.6 m, 0.76 m, 0.9 m, 1.2 m) |
| <b>3-Layer Vinyl</b>             | Table           | Excellent electrical properties, thickness 0.138 in. (3.5 mm)                                                                                | Gray, Blue, Brown | 8200 Series                                                                      | 4 x 10 <sup>7</sup>    | 1 x 10 <sup>7</sup>    | 2 ft., 2.5 ft., 3 ft., 4 ft. (0.6 m, 0.76 m, 0.9 m, 1.2 m) |
| <b>Conductive Plastic/Rubber</b> | Floor           | Conductive, resistant to heat and most common solvents, thickness 0.125 in. (3.2 mm)                                                         | Black             | 1864                                                                             | 6 x 10 <sup>2</sup>    | 9 x 10 <sup>2</sup>    | 2 ft. (0.6 m)                                              |
| <b>Anti-Fatigue</b>              | Floor           | Durable rubber “cells” construction, static control and minimize fatigue, thickness 0.625 in. (1.6 mm)                                       | Black             | 9900 Series                                                                      | <1 x 10 <sup>6</sup>   | <2 x 10 <sup>6</sup>   | 3 ft. (0.9 m)                                              |
| <b>Standard</b>                  |                 |                                                                                                                                              |                   |                                                                                  |                        |                        |                                                            |
| <b>Ultra R-2 Layer Rubber</b>    | Table           | Resistant to heat and chemicals, excellent electrical properties, thickness 0.060 in. (1.5 mm)                                               | Gray, Blue, Green | RM (W in. x L in.) L2RGR<br>RM (W in. x L in.) L2RBL<br>RM (W in. x L in.) L2RGN | 1 x 10 <sup>6</sup>    | 1 x 10 <sup>7</sup>    | 2 ft., 2.5 ft., 3 ft., 4 ft. (0.6 m, 0.76 m, 0.9 m, 1.2 m) |
| <b>3-Layer Vinyl</b>             | Table           | Excellent electrical properties, thickness 0.125 in. (3.2 mm)                                                                                | Gray, Blue        | TM (W in. x L in.) L3GR<br>TM (W in. x L in.) L3BL                               | 1 x 10 <sup>7</sup>    | 1 x 10 <sup>7</sup>    | 2 ft., 2.5 ft., 3 ft., 4 ft. (0.6 m, 0.76 m, 0.9 m, 1.2 m) |
| <b>Economy</b>                   |                 |                                                                                                                                              |                   |                                                                                  |                        |                        |                                                            |
| <b>1-Layer Vinyl</b>             | Table and Floor | Good lay flat characteristics, low cost, thickness 0.093 in. (2.4 mm) Not compatible with monitors                                           | Gray, Blue        | TM (W in. x L in.) L1GR<br>TM (W in. x L in.) L1BL                               | 1 x 10 <sup>9-10</sup> | 1 x 10 <sup>9-10</sup> | 2 ft., 2.5 ft., 3 ft., 4 ft. (0.6 m, 0.76 m, 0.9 m, 1.2 m) |
| <b>Conductive Rubber</b>         | Floor           | Conductive, resistant to heat and solvents, thickness 0.060 in. (1.5 mm), low cost                                                           | Black             | COND (W in. x L in.) FM                                                          | 1 x 10 <sup>5-6</sup>  | 1 x 10 <sup>5-6</sup>  | 2 ft., 3 ft., 4 ft. (0.6 m, 0.9 m, 1.2 m)                  |
| <b>Anti-Fatigue</b>              | Floor           | Foamed vinyl, static control and minimize fatigue, thickness 0.375 in. (9.5 mm)                                                              | Brown, Gray       | AFM (W in. x L in.) L1VBR<br>AFM (W in. x L in.) L1VGR                           | 1 x 10 <sup>9-10</sup> | 1 x 10 <sup>9-10</sup> | 3 ft. (0.9 m)                                              |