

TRI-450B Series

TRITAN™ 450 Multi-LED, Broad-Beam Blue Light Lamp

(U.S. patent no. 5,905,268; foreign patents pending)

Feature three cool-running, ultra-high flux 450 nm blue light LEDs with a broad-beam configuration. This powerful lamp provides a wider coverage area than conventional inspection lamps, while its compact head design allows access into areas inaccessible to larger inspection lamps. Ideal for most non-destructive testing applications.



- Nominal steady-state blue light intensity of $9,500 \mu\text{W}/\text{cm}^2$ at 15 inches (38 cm)
- Large 5 inch (13 cm) diameter coverage area at 15 inches (38 cm) with a minimum intensity of $2,000 \mu\text{W}/\text{cm}^2$
- Rubber bumper with patented thin-film dichroic lens filters out long-wave visible light
- Electronic Intensity Stabilizer ensures consistent LED performance
- Built-in fans keep LEDs cool to maintain optimum light output during extended use
- Instant-on operation. Lamp reaches full intensity immediately!
- Rugged, ergonomic, angled lamp body provides safe, fatigue-free handling
- Choice of standard 8 foot (2.4 m) or extra-long 20 foot (6.1 m) heavy-duty power cord with AC plug and rubber boot. Also available: Optional in-line power supply or industrial power supply with cord sets (sold separately).
- Includes fluorescent-enhancing, yellow spectacles and soft carrying case





Also Available:

TRITAN™ 450MB portable, battery-operated AC/DC lamp kit. Includes TRITAN 450 blue light LED lamp, rechargeable NiMH battery pack, power supply adapter with AC and DC cord sets, smart AC charger, fluorescent-enhancing, yellow spectacles and soft, lightweight carrying case.

LAMP SPECIFICATIONS

Style	Pistol grip
Light Source	3 blue light LEDs
Lamp Head Diameter	5 in (13 cm)
Length	8.0 in (20.3 cm)
Weight	1 lb (454 g)
Power Requirements:	
AC lamp	(TRI-450B) 120VAC*
AC/DC lamp	(TRI-450MB) 120VAC*/12VDC
Battery Pack:	
Type	12V, NiMH (rechargeable)
Run Time	3.5 hours (continuous)
Charge Time	2 hours

*Also available in 230V, 240V and 100V versions.



Replacement Parts & Accessories

129141	Standard, 8 foot (2.4 m) AC power cord
129145	Extra-long, 20 foot (6.1 m) AC power cord
129162	3.5 foot (1.1 m) DC power cord for "M" series lamps
127933	Particulate filter assembly
BP-30	Battery pack with 12V rechargeable NiMH battery
BR-150A	Smart AC charger
CC-370A	Soft carrying case
FP-450	Rubber bumper with dichroic lens
PSA-250A	AC/DC power supply adapter for "M" series lamps
PS-200A	Industrial power supply. Primary cord: 8 feet (2.4 m); secondary cord: 20 feet (6.1 m).
PS-300A	In-line power supply. Primary cord: 8 feet (2.4 m); secondary cord: 8 feet (2.4 m).
UVS-40	Fluorescent-enhancing spectacles, yellow

BLUE LIGHT BEAM PROFILE

