VISES, MAGNETS & CLAMPS

QUICK-GRIP® ONE-HANDED MICRO BAR CLAMP/SPREADER

- One-handed Quick-Release[™] trigger allows for fast and easy positioning
- · Perfect size for hobby and craft applications
- Converts to a spreader by reversing the clamp pads





XPTM ONE-HANDED BAR CLAMP & SPREADER

- I-beam bar resists twisting and bowing
- Power Locks[™] hold better, allowing for up to 600 lbs. of force
- Quick-ChangeTM jaw, converts clamp to spreader quickly
- Non-marring pads grip securely
- Quick-Release™ trigger

Model No.	Mfg. No.	Clamping Capacity	Spreading Capacity	Throat Depth	Price /Each
TKZ880	2021406	6" (15 cm)	7 1/2"-14 5/8" (190 mm-371 mm)	3 1/4" (83 mm)	
TKZ881	2021412	12" (30 cm)	7 1/2"-20 5/8" (190 mm-523 mm)	3 1/4" (83 mm)	
TKZ882	2021418	18" (45 cm)	7 1/2"-26 5/8" (190 mm-676 mm)	3 1/4" (83 mm)	
TKZ883	2021424	24" (60 cm)	7 1/2"-32 5/8" (190 mm-828 mm)	3 1/4" (83 mm)	
TKZ884	2021436	36" (91 cm)	7 1/2"-44 5/8" (190 mm-1133 mm)	3 1/4" (83 mm)	
TKZ885	2021450	50" (127 cm)	7 1/2"-58 5/8" (190 mm-1489 mm)	3 1/4" (83 mm)	

Clamping

Capacity

24" (60 cm)

48" (115 cm)



PARALLEL JAW CLAMPS

- Deep 3 3/4" jaw depth for optimized pressure distribution
- · Secure locking system prevents jaws from slipping
- ProTouch handle for an ergonomic grip

Mfg.

2026500

2026501

No.

- · Resin body and jaws prevents
- marring and glue adhesion • Up to 1150 lbs. of pressure

Model

TLY300

TLY301





PARALLEL JAW CLAMPS

- Aluminum die-cast handles have a quick adjustment mechanism for easy sizing
- Serrations in the steel rails engage with a hardened steel insert in the jaw to eliminate slipping
- Clamp jaws are encased in non-marring, glue resistant polypropylene casing
- Clamps up to 2.5 KN of pressure



Model No.	Clamping Capacity	Throat Width	Throat Depth	Price /Each
TYB500	24"	1 1/2"	3 1/3"	
TYB501	50"	1 1/2"	3 1/3"	



TOOLS &

1.888.610.7664

www.calcert.com