


ULTRAPROBE® 100

**Analog Ultrasonic Inspection System
Saves Money, Energy and Time!**



**Why Ultrasound Technology is the
smart approach to inspection:**

- Ultrasound is very directional and localized
- Ultrasound can be easily blocked or shielded
- Ultrasound instruments can be used in noisy environments
- Changes in Ultrasound provide early warning of potential problems
- Ultrasound instruments are **easy** to use!

The Ultraprobe® 100 is a practical tool for *any* leak detection, steam trap inspection or mechanical troubleshooting program. Simple to use — find compressed air and steam leaks and prevent machinery failure with this unique instrument.



Ultraprobe 100 testing pump valve leaks

The Ultraprobe 100 features an 8-position sensitivity dial with decibel indications. In addition, it features an LED bar graph display in which each LED equals approximately 3 dB — ideal for calculating decibel levels.



Pneumatic testing



Tests steam traps

ue
SYSTEMS INC
The ultrasound approach

ULTRAPROBE® 100 KIT Application Selection Chart



Ultraprobe® 100 KIT

UP100KT

Ultraprobe 100 Kit

- UP 100 Pistol with LED Bar Graph Meter
- 8 Position Sensitivity Selection
- Scanning Module
- Rubber Focusing Probe
- Stethoscope Module
- Warble Tone Generator (WTG-1) with Battery Recharger
- Lightweight "Walkman"-Style Headset
- 9 Volt Alkaline Battery (Replaceable)
- Nylon Cordura Soft Carrying Case
- Comprehensive Instruction Manual

UP100SC

Ultraprobe 100 Stethoscope/Scanner Kit

Includes scanning module & stethoscope module.

UP100S

Ultraprobe 100 Scanner Kit

Includes scanning module & rubber probe.

UP100C

Ultraprobe 100 Stethoscope Kit

Includes contact module.



APPLICATION	KIT #	UP100KT	UP100SC	UP100S	UP100C
Pressure & Vacuum Leak Detection		✓	✓	✓	
Valve Seat Leak Detection		✓	✓		✓
Exhaust System Leaks		✓	✓	✓	
Heat Exchangers, Boilers, Condensers		✓	✓	✓	
Steam Trap Inspection		✓	✓		✓
Bearing Testing		✓	✓		✓
Gear/Gear Box Inspection		✓	✓		✓
Wind Noise/Water Leaks/Hatches		✓			
General Mechanical Inspection & Trouble Shooting		✓	✓		✓
Tanks, Pipes, Leak Testing, etc.		✓	✓	✓	
Electrical Inspection		✓	✓	✓	

Available Accessories (Call, fax or e-mail for information)

- Holster Set
- Stethoscope Extension Kit
- Speaker Amplifier
- LRM-1 Long Range Module
- Specialized Tone Generators (Used instead of pressure test, transmits ultrasound through a leak – Fast & Easy!)
- DHC-2H Deluxe Noise Isolating Headset

ULTRAPROBE® 100 Specifications

Construction:	Hand-held ABS pistol type ultrasonic processor, stainless steel sensor enclosures
Circuitry:	SMD/Solid State hybrid heterodyne receiver
Frequency Range:	35-45 kHz
Indicator:	10 segment LED Bar Graph (red)
Sensitivity Selection:	8 position precision attenuation
Power:	9 Volt Alkaline Battery
Low Battery Voltage Indicator:	LED
Headset:	Weight: 2.5 oz. Operating Temperature Range: -22° to 167° F (-30° to +75° C) Cable: 48" shielded Cable Pull: 20 lbs. Frequency Range: 300 to 3000 Hz Impedance: 150Ω Molded Connector
Probes:	Scanning Module (SCM-1) Stainless Steel Unisonic (single transducer) piezo electric crystal type; Stethoscope/Contact Module (STM-1) , Stainless Steel plug-in type with 5.5", Stainless Steel Waveguide Rubber Focusing Probe Shields stray ultrasonic signals and focuses detected signals
Transmitter:	Patented warble tone transmission
Response time:	300 msec
Ambient Operating Temperature Range:	32°-120° F (0-50° C)
Relative Humidity:	10-95% non-condensing at up to 86° F (30° C)
Storage Temperature:	0°-130° F (18°-54° C)
Warranty:	1-year parts/labor standard, (details available on request). 5 years with completed warranty registration card.
Dimensions:	5.25" x 2" x 8" (13.3 x 5 x 20.3 cm)
Weight:	11 oz (.3 kg)
Carrying Case:	Nylon Cordura soft carrying case

Ultraprobe 100 Kit: Meets and exceeds ASTM E1002-2005 requirements for Leak Detection.
Covered by one or more of the following patents: 0151115; 0303776; 0315199; 1206586; 1297576; 1881263; 2562758; 2689339; 4416145; 4823600; 5955670; 6122966; 6339961; 6341518; 6415645; 6655214; 6707762; 6804992
 UE Systems is committed to continual product improvement; therefore specifications are subject to change without notice. Warranty details are available by request.