

Part No.

# USN0-2MNPT-MP

*Male USN0 Probe x 1/4" Male NPT, 316 S.S.*

Quick-connect rated to 10,000 psi. Self locking so when pressure increases above 50 psi the Quick-connect cannot be disassembled.



USN0-2MNPT-MP

## Specs/Attributes

|                           |                                                                    |
|---------------------------|--------------------------------------------------------------------|
| Burst Pressure            | 40000 PSI / 2760 bar / 275 MPa                                     |
| Country of origin         | USA                                                                |
| Materials                 | 316 Stainless Steel                                                |
| Max Operating Temperature | 200 °F / 93 °C                                                     |
| Max Pressure              | 10000 PSI / 700 bar / 70 MPa                                       |
| Media Compatibility       | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water            |
| Min Operating Temperature | -15 °F / -26 °C                                                    |
| Process Connection        | 1/4" Male NPT (ASME B1.20.1)                                       |
| Wrench Size               | 9/16 In<br>14 mm                                                   |
| Connector End 1           | Male USN0 Probe                                                    |
| Weight                    | 1.54 oz / 44 grams                                                 |
| Dimensions                | H: 2.53 in (6.43 cm) x W: 0.56 in (1.42 cm) x D: 0.65 in (1.65 cm) |