


**UNI-T**<sup>®</sup>

Instruments.uni-trend.com



# Data Sheet

## UTG2000X Series Function/Arbitrary Waveform Generator

V 1.1


July 2024

## Product Features


- Dual channel with a maximum frequency output of 120 MHz and a maximum output amplitude of 20 Vpp.
- 625 MSa/s sample rate and 16-bit vertical resolution
- Multiple analog and digital modulation function: AM, PM, FM, DSB-AM, ASK, PSK, BPSK, QPSK, FSK, 3FSK, 4FSK, QAM, OSK, PWM, and SUM
- Square wave with the maximum frequency of 50 MHz and low jitter
- Wide dynamic and high-precision pulse wave with adjustable edge time, which can achieve fine edge time adjustment and has extremely high adjustment resolution and range
- Excellent performance with low harmonic distortion
- Supports frequency sweep and burst output
- A low-jitter waveform can be generated point by point, with an arbitrary waveform length ranging from 8 points to 64 megapoints (Mpts)
- Supports channel copying, following, and stacking settings
- Can generate arbitrary waveform through arbitrary waveform editor on the upper computer
- 7-bit hard frequency counter
- Built-in 200 arbitrary waves
- Standard USB Host, USB Device, and LAN interface
- Support SCPI (programmable instrument standard commands)
- 4.3 inch TFT LCD capacitive touch display screen

## Design Features



### Equivalent performance of double channel output




### Low Jitter




### Low Distortion Output



### High Signal to Noise Ratio




### Burst




Three types of bursts: "N cycle," "Infinite," and "Gate." Three trigger sources: "Internal," "External," and "Manual."

## Pulse Wave and Edge Time




The new generation of wide dynamic, high-precision, edge-time adjustable pulse wave has a minimum pulse width of 8 ns. The pulse width can be fine adjusted and the minimum step is 100 ps. In addition, it can produce higher harmonic component, which has the feature of a dedicated pulse generator. The edge time can be independently set to a minimum of 5 ns.

## Sweep Frequency




Three sweep frequency modes: "Line", "Log" and "Step". Three trigger sources: "Internal", "External" and "Manual".

## Channel Merge



Channel merging can be realized with SUM or channel stacking functions, generating signals with adjustable signal-to-noise ratios and dual-tone multi-frequency signals. Up to four signals can be summed and coupled on two channels, and SUM enables the output of two-tone or multi-tone signals.

## Multiple Modulation Function



Modulation output (15 types): AM, FM, PM, DSB-AM, ASK, FSK, PSK, 3FSK, 4FSK, BPSK, QPSK, OSK, SUM, QAM and PWM.

## Frequency Counter



The high precision hardware frequency counter can measure the frequency range of 100 mHz to 200 MHz.




## Channel Tracking




Channel tracking simplifies the operation of dual channels. The phase, amplitude and frequency of both channels can be controlled by a single parameter, making it easy to create deviation or tracking signals.

## Arbitrary Waveform Editor



The arbitrary waveform editor offers diverse generation methods. Arbitrary waveforms can be created by inserting standard waveforms or drawing freely.

## Remote Control



The instrument can connect to the computer via USB and LAN port and it supports remote control. Users can use the control software for remote operation and control, enabling automatic testing and remote monitoring.

#### 4. 3inch Capacitive Touch Screen



4.3-inch high-definition display with touch operation, making instrument control faster and more convenient.

## Definition and Condition

- "Technical Index" provide a detailed description of the performance of the parameters which involved in the product warranty. Unless otherwise specified, these specifications are applicable to the temperature range from 18 °C to 28 °C.
- "Typical Value" refers to other product performance information which not covered in the product warranty. When performance exceeds the technical index, 80% of the units can exhibit 95% confidence in the temperature range of 18 °C to 28 °C. Typical performance does not include uncertainty of measurement.
- "Nominal Value" means the expected performance or describes the performance of the product that is useful in the application of the product but is not included in the scope of the product warranty.

Under the following conditions, it can achieve its technical indicators:

Within the calibration cycle and after being warmed up for at least 30 minutes. If the device is stored in an environment that is within the allowable storage temperature range but exceed the allowable operating temperature range, the instrument must be placed within the allowable operating temperature range for at least two hours

## Basic Waveform Characteristics

All analog channel output related specifications is suitable for channel 1 and channel 2

Basic characteristics		
Model	UTG2062X	UTG2082X
Channel	Dual channel	
Sampling rate	625 MSa/s (1.25 GSa/s, 2 x interpolation)	
Vertical resolution	16-bit	
Working modes	Continuous, Modulation, Frequency sweep, Burst, and Counter	
Wave	Sine, Square, Ramp, Pulse, Noise, DC, Arb, Harmonic, PRBS, Expression, and Double pulse	
Modulation	AM, FM, PM, DSB-AM, ASK, FSK, PSK, 3FSK, 4FSK, BPSK, QPSK, OSK, SUM, QAM, and PWM	
Frequency sweep	Lin, Log, and Step	
Burst	N-cycle, Gated, and Infinite	
Counter	100 mHz to 200 MHz, 7 digits	
LCD	4.3 inch TFT LCD capacitive touch display screen, WVGA (480×272)	

Frequency characteristic			
Sine wave	1 µHz to 60 MHz	1 µHz to 80 MHz	1 µHz to 120 MHz
Square wave	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
pulse wave	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
Ramp wave	1 µHz to 3 MHz	1 µHz to 4 MHz	1 µHz to 5 MHz
Arbitrary wave	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
Harmonic	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
Expression	1 µHz to 15 MHz	1 µHz to 20 MHz	1 µHz to 25 MHz
PRBS	1 µbps to 30 Mbps	1 µbps to 40 Mbps	1 µbps to 50 Mbps
Gauss noise	1 MHz to 60 MHz	1 MHz to 80 MHz	1 MHz to 120 MHz
Resolution	1 µHz		
Frequency: 10.0000 MHz			
Reference frequency	Initial accuracy: ±0.5 ppm, 25°C		
	Temperature stability: ±0.5 ppm, 0°C to 40°C		
	Annual aging rate: ±1 ppm, First year aging rate		
Sine wave			
Frequency	1 µHz to 60 MHz	1 µHz to 80 MHz	1 µHz to 120 MHz
		DC to 1 MHz: -70 dBc	
		1 MHz to 10 MHz: -65 dBc	
Harmonic distortion	Typical value (0 dBm)		
	10 MHz to 40 MHz: -60 dBc		
	40 MHz to 80 MHz: -55 dBc		
	80 MHz to 120 MHz: -50 dBc		
THD	< 0.07% (DC to 20 kHz, 1 Vpp)		
Spurious signal (anharmonic)	Typical value (0 dBm)		
	≤10 MHz, < -70 dBc >10 MHz, <-70 dBc+6 dB/octave		
Phase noise(typical)	10 MHz: ≤-125 dBc/Hz (typical, 0 dBm, 10 kHz deviation)		
Square wave			
Frequency	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
Rise/fall time (1 Vpp, 50 Ω)	<7 ns (typical, 1 kHz)	<6 ns (typical, 1 kHz)	<5 ns (typical, 1 kHz)
Overshoot (100kHz, 1 Vpp)	< 2% (typical, 50 Ω)		
Duty ratio	0.001% to 99.999% (limited by current frequency)		
Symmetry (duty ratio=50%)	1% of period + 4 ns		
Jitter(RMS) (1 Vpp ,	Typical (1 MHz,	≤ 5 MHz:2 ppm + 200 ps	

50 Ω)	1 Vpp, 50 Ω)	> 5 MHz:200 ps
<b>Ramp wave</b>		
Frequency	1 μHz to 3 MHz	1 μHz to 4 MHz
Non-linearity	< 1% of peak output (typical value, 1 kHz, 1 Vpp, symmetry 100%)	
Symmetry	0.0% to 100.0%	
<b>Pulse wave</b>		
Frequency	1 μHz to 30 MHz	1 μHz to 40 MHz
Minimum pulse width	8 ns	
Variable edge	7 ns to 10 s	6 ns to 10 s
Duty ratio	0.001% to 99.999% (limited by current frequency)	
Overshoot	< 2% (typical, 1 Vpp 50 Ω)	
Jitter	150 ps	
<b>Arbitrary wave</b>		
Frequency (DDS)	1 μHz to 30 MHz	1 μHz to 40 MHz
	DDS	
Wave length	Point by point	
	8 pts to 32 Mpts (Up to 64 Mpts for single channel output)	
Vertical resolution	16-bit (symbol included)	
Sampling rage	DDS	625 MSa/s (DDS)
	Point by point	
Sampling rage	1 μSa/s to 312.5 MSa/s	
Minimum rise/fall time	<5 ns (typical, 1 Vpp, 50 Ω)	
Jitter (playback mode)	150 ps	
Nonvolatile storage	200 waves	
<b>PRBS</b>		
Bit rate	1 μbps to 30 Mbps	1 μbps to 40 Mbps
Edge time	7 ns to 1,000 s	6 ns to 1,000 s
Symbol	PN3, PN5, PN7, PN9, PN11, PN13, PN15, PN17, PN19, PN21, PN23, PN25, PN27, PN29, PN31	
<b>Expression properties</b>		
Frequency	1 μHz to 15 MHz	1 μHz to 20 MHz
Function	Sin, cos, tan, sinc, abs, ln, sqrt, acos, asin, atan, sinh, tanh, ceil, exp, fabs, floor, lg, cosh	
Operation	+, -, *, /, ^	
Variable value	°, rad	

**Harmonic**

Frequency	1 µHz to 30 MHz	1 µHz to 40 MHz	1 µHz to 50 MHz
Harmonic order	2 to 16		
Type	Odd, Even, All, User Defined		
Amplitude	1 mV to 10 Vpp (50 Ω)		
	Set the amplitude based on the selected harmonic sequence number		
Phase	-360° to 360°		
	Set the phase based on the selected harmonic sequence number		

**Double Pulse**

Trigger Source	Internal, external, manual
Delay	0 to 100 s
Total number	2 to 30
Minimum pulse width	20 ns
Variable edge	5 ns to 500 s
Pulse gap	20 ns to 1 ks

**Output Characteristic****Output**

Amplitude (50 Ω)	≤20 MHz: 1 mVpp to 10 Vpp ≤60 MHz: 1 mVpp to 5 Vpp ≤120 MHz: 1 mVpp to 2 Vpp
Amplitude (High resistance)	≤20 MHz: 2 mVpp to 20 Vpp ≤60 MHz: 2 mVpp to 10 Vpp ≤120 MHz: 2 mVpp to 4 Vpp
Accuracy	Typical value (1kHz, sine wave, 0V, deviation, <math>\pm (1\% \text{ of set value} + 1 \text{ mVpp})</math> > 10 mVpp)
Amplitude flatness	Typical value (1kHz, sine wave, 1 Vpp) ≤60 MHz: ±0.2 dB ≤80 MHz: ±0.4 dB ≤120 MHz: ±0.6 dB

**DC offset**

Range(peak AC+DC)	±5 V (50 Ω) ±10 V (High resistance)
Accuracy of offset	Offset set value ±1% ± amplitude set value 0.5% ±2 mV

**Waveform output**

Impedance	50 Ω typical value
Protection	Overvoltage protection, overload automatically disabling waveform output

**Modulation Types**

Model	UTG2062X	UTG2082X	UTG2122X
<b>AM</b>			
Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave		
Source	Internal/External		
Modulation wave	Sine wave, square wave, ramp wave, noise, and arbitrary wave		
Modulation depth	0% to 120%		
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)		
<b>FM</b>			
Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave		
Source	Internal/External		
Modulation wave	Sine wave, square wave, ramp wave, noise, and arbitrary wave		
Frequency deviation	DC to 30 MHz	DC to 40 MHz	DC to 60 MHz
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)		
<b>PM</b>			
Carrier wave	Sine wave, square wave, ramp wave, and arbitrary wave		
Source	Internal/External		
Modulation wave	Sine wave, square wave, ramp wave, noise, and arbitrary wave		
Phase deviation	0 to 360°		
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)		
<b>DSB-AM</b>			
Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave		
Source	Internal/External		
Modulation wave	Sine wave, square wave, ramp wave, noise, and arbitrary wave		
Modulation depth	0% to 100%		
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)		
<b>ASK</b>			
Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave		
Source	Internal/external		
Modulation wave	Square wave (Duty ratio 50%)		

Modulation frequency 2 mHz to 1 MHz (The modulation source is internal)

### FSK

Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave
Source	Internal/external
Modulation wave	Square wave (Duty ratio 50%)
Hopping frequency	Carrier Frequency
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)

### PSK

Carrier wave	Sine wave, square wave, ramp wave, and arbitrary wave
Source	Internal/external
Modulation wave	Square wave (Duty ratio 50%)
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)
Phase	-360° to 360°

### 3FSK

Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave
Source	Internal
Modulation wave	Square wave (Duty ratio 50%)
Hopping frequency	Carrier Frequency
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)

### 4FSK

Carrier wave	Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave
Source	Internal
Modulation wave	Square wave (Duty ratio 50%)
Hopping frequency	Carrier Frequency
Modulation frequency	2 mHz to 1 MHz (The modulation source is internal)

### BPSK

Carrier wave	Sine wave, square wave, ramp wave, and arbitrary wave
Source	Internal
Symbol	PN3, PN5, PN7, PN9, PN11, PN13, PN15, PN17, PN21, PN23, PN25, PN27, PN29, and PN31
Symbol bit rate	2 mbps to 1 Mbps (The modulation source is internal)
Phase	-360° to 360°

### QPSK

Carrier wave	Sine wave, square wave, ramp wave, and arbitrary wave
Source	Internal
Symbol	PN3, PN5, PN7, PN9, PN11, PN13, PN15, PN17, PN21, PN23, PN25,

PN27, PN29, and PN31

Symbol bit rate 2 mbps to 1 Mbps (The modulation source is internal)

Phase -360° to 360°

**OSK**

Carrier wave Sine wave

Source Internal/external

Oscillation time 5 ns to 250 s

Modulation frequency 2 mHz to 1 MHz (The modulation source is internal)

**SUM**

Carrier wave Sine wave, square wave, ramp wave, arbitrary wave, pulse wave, harmonics, and noise

Source Internal/External

Modulation wave Sine wave, square wave, ramp wave, noise, and arbitrary wave

Modulation depth 0% to 100%

Modulation frequency 2 mHz to 1 MHz (The modulation source is internal)

**QAM**

Carrier wave Sine wave

Constellation mapping QAM4, QAM8, QAM16, QAM32, QAM64, QAM128, and QAM256

Symbol PN3, PN5, PN7, PN9, PN11, PN13, PN15, PN17, PN21, PN23, PN25, PN27, PN29, and PN31

Symbol bit rate 2 mbps to 1 Mbps

**PWM**

Carrier wave Pulse

Source Internal/external

Modulation wave Sine wave, square wave, ramp wave, noise, and arbitrary wave

PWM range 0% to 49.99%

Modulation frequency 2 mHz to 1 MHz (The modulation source is internal)

**Sweep****Frequency sweep**

Carrier wave Sine wave, square wave, ramp wave, arbitrary wave, and pulse wave

Type Linear, Logarithmic, and Stepwise

Trigger Source Internal, external, and manual

Trigger Edge Rising edge, falling edge

Trigger Output ON, OFF

Frequency sweep time	1 ms to 500 s $\pm$ 0.1% (Lin, Log)
Residence time	1 ms to 500 s $\pm$ 0.1% (step)
Step number	2 to 2,048 step

## Burst

Burst	
Waveform	Sine wave, square wave, ramp wave, pulse, and arbitrary wave
Mode of pulse train	N cycle, infinite, and gated
Initial and stop phase	-360° to 360°
Source	Manual, external, and internal
Trigger edge	Rising edge/falling edge
Trigger Output	ON, OFF
Internal cycle	1 us to 500 s $\pm$ 0.1%
Recurring number	1 to 50,000
Polarity	Positive and negative (TTL level input)

## Auxiliary functions

Channel settings	
Channel output	ON, OFF
Channel reverse	ON, OFF
Synchronous output	CH1, CH2, and OFF
Load	50 Ω, 75 Ω, HighZ, and Custom (1 Ω to 999999 Ω)
Amplitude limitation	ON, OFF
Upper limit of amplitude	-9.998 V to 10 V (HighZ)
Lower limit of amplitude	-10 V to 9.998 V (HighZ)
Channel replication	
Channel 1 replication	CH1→CH2
Channel 2 replication	CH2→CH1
Channel Follow	
Follow type	Parameter following, channel tracking
Parameter follow	Frequency following, amplitude following, and phase following
Follow type	Deviation, Ratio
Channel stacking	
Channel 1 overlay	ON, OFF

Channel 2 overlay	ON, OFF
-------------------	---------

### System settings

Language	English, Chinese, and Deutsch
Phase synchronization	Independent, synchronized
Voice	ON, OFF
Number separator	Comma, space, and none
Backlight	10%, 30%, 50%, 70%, 90%, and 100%
Screen saver	Off, 5 minutes, 15 minutes, 30 minutes, and 1 hour

### Frequency meter

Measurement frequency range	100 mHz to 200 MHz
Input Level Range	TTL compatibility
Measurement accuracy	7 digits

## Interface and Display

### Interface

Standard configuration	USB Host, USB Device, and LAN
------------------------	-------------------------------

### Synchronous signal output

Output level	TTL compatible
Frequency	1 µHz to 10 MHz
Output Impedance	50 Ω (Typical)
Coupling method	DC

### External modulation input

Input frequency	<50 KHz
Depth	±5 Vpk=100%
Impedance	5 kΩ (Typical)

### External reference input

Input frequency	10 MHz ± 50Hz
Input level	TTL compatible
Impedance	10 kΩ (Typical value, DC coupling)
Lock time	<1 s

### Internal reference output

Input frequency	10 MHz
Input level	TTL compatible
Impedance	50 Ω (Typical value, DC coupling)

**Trigger Input**

Input level	TTL compatible
Slope	Rising or falling
Pulse width	>100 ns
Impedance	10 kΩ (Typical value, DC coupling)
Response time	<1 us (Typical value)

**Trigger Output**

Input level	TTL compatible
Pulse width	>400 ns (Typical value)
Impedance	50 Ω (Typical value)

**Display screen**

Display type	4.3 inches TFT LCD Capacitive Touch Screen
Display resolution	WVGA (480×272)

**General Technical Specifications****Specifications**

Supply voltage	100 to 240 VAC (Fluctuations: ±10%), 50 Hz/60 Hz; 100 to 120 VAC (Fluctuations: ±10%), 400 Hz
Power consumption	< 50 W
Fuse	2.5 A, Class T, 250 V

**Environment**

Temperature range	Operation: +10 °C to +40 °C Non operational: -20 °C to +60 °C
Cooling method	Natural cooling
Humidity range	+35 °C Below: ≤90% relative humidity +35 °C to +40 °C: ≤60% relative humidity
Altitude	Operating below 2, 000 m Non-operating below 15, 000 m
Class of pollution	2
Operating environment	Indoor

**Mechanical specifications**

Dimensions	215mm×103mm×316mm (Width x Height x Length)
Net weight	2.5 kg
Calibration cycle	The recommended calibration cycle is one year

**Regulatory standards**

EMC	Compliance with EMC directives (2014/30/EU), Conform to or better than IEC 61326-1:2021/EN61326-1:2021, IEC 61326-2-1:2021/EN61326-2-1:2021	
Conductive disturbance	CISPR 11/EN 55011	CLASS B group 1, 150 kHz-30 MHz
Radiation disturbance	CISPR 11/EN 55011	CLASS B group 1, 30 MHz-1 GHz
Electrostatic discharge (ESD)	IEC 61000-4-2/EN 61000-4-2	4.0 kV (Contact), 8.0 kV (air)
Radio frequency electromagnetic field immunity	IEC 61000-4-3/EN 61000-4-3	0 V/m (80 MHz to 1 GHz); 3 V/m (1.4 GHz to 2 GHz); 1 V/m (2.0 GHz to 2.7 GHz)
Electrical fast transient burst (EFT)	IEC 61000-4-4/EN 61000-4-4	2 kV (AC input port)
Surge	IEC 61000-4-5/EN 61000-4-5	1 kV (Live line to zero line) 2 kV (Fire/zero line to ground)
Immunity to RF continuous conduction	IEC 61000-4-6/EN 61000-4-6	3 V, 0.15-80 MHz
Voltage dips and short interruptions	IEC 61000-4-11/EN 61000-4-11	Voltage dip: 0% UT during 1 cycle; 40% UT during 10/12 cycles; 70% UT during 25/30 cycles Short Interruption: 0% UT during 250/300 cycles

### Safety regulations

EN 61010-1:2010+A1:2019  
 EN IEC61010-2-030:2021+A11:2021  
 BS EN61010-1:2010+A1:2019  
 BS EN IEC61010-2-030:2021+A11:2021  
 UL 61010-1:2012 Ed.3+ R:19 Jul2019  
 UL 61010-2-030:2018 Ed.2  
 CSA C22.2#61010-1:2012 Ed.3+U1;U2;A1  
 CSA C22.2#61010-2-030:2018 Ed.2

## Ordering Information

	Description	Order No.
Models	Maximum output frequency 60 MHz	UTG2062X
	Maximum output frequency 80 MHz	UTG2082X
	Maximum output frequency 120 MHz	UTG2122X
Standard accessories	Power cord x 1	
	USB cable x 1	UT-D14
	BNC-BNC x 1	UT-L45
Recommended options	BNC--red and black alligator clip cable x1	UT-L02A
	10 W Power amplifier option	UT-M14

Remarks: All mainframes, accessories, and optional items can be ordered from the local UNI-T distributor.

## Limited Warranty and Liability

Uni-T guarantees that the Instrument product is free from any defect in material and workmanship within three years from the purchase date. This warranty does not apply to damages caused by accident, negligence, misuse, modification, contamination or improper handling. If you need warranty service within the warranty period, please contact your seller directly. Uni-T will not be responsible for any special, indirect, incidental or subsequent damage or loss caused by using this device. For the probes and accessories, the warranty period is one year. Visit [instrument.uni-trend.com](http://instrument.uni-trend.com) for full warranty information.



Register your product to confirm your ownership. You will also get product notifications, update alerts, exclusive offers and all the latest information you need to know.

**UNI-T** is the licensed trademark of UNI-TREND TECHNOLOGY CO., Ltd. The product information in this document subject to update without notice. For more information on UNI-T Test & Measure Instrument products, applications or service, please contact UNI-T instrument for support, the support center is available on [www.uni-trend.com](http://www.uni-trend.com) ->[instruments.uni-trend.com](http://instruments.uni-trend.com)  
<https://instruments.uni-trend.com/ContactForm/>